XEROX

Material Safety Data Sheet

MSDS No: S-9501 10/26/04 Date: Revision: N/A

Manufacturer: Xerox Corporation, Office Group

Telephone # (s): P.O. Box 1000

Health Emergency: (585) 422-2177

Wilsonville, Oregon 97070-1000

Transportation Emergency (Chemtrec): (800) 424-9300

Section I - Product Identification

Trade Names/Synonyms: WorkCentre C2424 Solid Ink Part No.: 108R660, 108R661, 108R662,

108R663, 108R664, 016-2096-00

Safety Information: (800) 828-6571

WHMIS Status: This is not a WHMIS controlled product

> <u>Ingredients (% by wt.)</u> CAS No. Polyethylene and fatty amide waxes **Proprietary** Resin **Proprietary** Dyes Proprietary

Section II - Emergency and First Aid

Primary Route of Entry: Symptoms of Overexposure:

None expected from several, repeated prolonged skin exposures. Skin

Eyes:

Contact unlikely. If particles get into eyes, flush

thoroughly with water. Medical Conditions Generally Aggravated by Exposure:

Skin: None when used as described by product literature.

Wash with thoroughly with soap and water.

Inhalation:

Not applicable **Additional Information:**

None. **Ingestion:**

Not applicable

Section III - Toxicology and Health Information

Oral LD₅₀: >5 g/kg (rats) practically non-toxic.

Dermal LD₅₀: N.D.

N.D.

Eye Irritation: N.D. **Skin Sensitization:** N.D.

Skin Irritation: Not a skin irritant

Human Patch:

Mutagenicity: Negative in a standard bacterial reverse mutation assay (Ames test).

Carcinogens: Components not listed by IRAC, NTP, or OSHA.

Aquatic LC₅₀:

Additional Information: None

¹XEL-Xerox Exposure Limit N.D. - No Data/Not determined N.A. – Not Applicable

XEROX Trade Name: WorkCentre C2424 Solid Ink MSDS No.: S-9501

Section IV - Physical Data

Appearance/Odor: Waxy solid. Black, blue, red or yellow

In color / faint odor

Boiling Point: N.A.
Solubility in Water: Insoluble
Evaporation Rate: N.A.
Vapor Density (Air=1): N.A.
Volatile: N.A.

Melting Point: $\sim 100^{\circ}\text{C} (212^{\circ}\text{F})$ Specific Gravity (H₂O=1): $\sim 1, @25^{\circ}\text{C} (77^{\circ}\text{F})$

Section V - Fire and Explosion Data

Flash Point (Method Used): >221 °C (>429°F), Pensky-Martens closed tester

Extinguishing Media: All extinguishing agents classified as B and C are effective, including dry powder(s), carbon

dioxide and halon.

Special Fire Fighting Procedures: Avoid inhalation of smoke. As in any fire, wear self-contained breathing apparatus, pressure

demand, MSHA/NIOSH approved, and full protective gear.

Fire and Explosion Hazards: These inks will burn. During a fire, irritating and toxic gases may be generated by thermal

decomposition or combustion.

Section VI -Reactivity Data

Stability: Stable

Hazardous Polymerization: Will Not Occur

Hazardous Decomposition Products: Material may decompose into toxic byproducts when heated to temperatures above 200°C

 $(392^{\circ}F)$

Incompatibility (Materials to Avoid): None known

Section VII - Special Protection Information

Respiratory Protection:None required when used as intended.Eye Protection:None required when used as intended.Protective Gloves:None required when used as intended.

Other: Wash skin thoroughly.

Section VIII - Special Precautions

Handling and Storage: No special precautions, when used as intended. Avoid high temperatures. Keep in below 60°C (140°F)

Conditions to Avoid: Temperatures above 200°C (392°F)

Section IX-Spill, Leak, and Disposal Procedures

For Spills or Leakage: N.A.

Waste Disposal Method: This product is not a hazardous waste as specified in 40CFR261. TCLP below hazardous waste levels

set by EPA. State and local waste disposal requirements, however, may be more restrictive. Manage

and dispose of waste in accordance with all federal, state, and local regulations.

Section X - Transportation Information

This product is <u>not</u> regulated as a hazardous material