Product Name: Print Cartridge Yellow Type MP C4500/C4540/LD445c MSDS Number: 841343 Date Prepared: 07/09/2005 Date Modified: 2009/04/08 Date: 18/08/2009



# Material Safety Data Sheet (ANSI form)

## Section1: Chemical Product and Company Identification

: Print Cartridge Yellow Type MP C4500/C4540/LD445c **Product Name** General Use The Image Formation of Printing Machine or Copier

MSDS Number : 841343

Company Name : Ricoh Americas Corporation

: Environment Safety Center, Corporate Environment Division : 146-1 Nishisawada, Numazu-shi, Shizuoka-ken, 410-0007 Japan Department Address

Telephone : 055-920-1470, Japan

Number

Telefax Number: 055-920-1479, Japan E-mail : msdsinfo@nts.ricoh.co.jp

## Section2: Composition, Information on Ingredients

Ingredients	Chemical	Contents	ACGIH	(TLV)		OSHA	(PEL)
CAS No./Common	Formula	(%)	TWA	STEL	С	TWA	С
Name							
Confidential	Confidential	>70	N.A	N.A	N.A	N.A	N.A
Polyester Resin							
68516-73-4	C34H32N6O	<10	N.A	N.A	N.A	N.A	N.A
	12						
Organic Pigment							
Confidential	Confidential	<10	N.A	N.A	N.A	N.A	N.A
Wax							
7631-86-9	O2Si	<10		N.A	N.A		N.A
Silica			10mg/m3			15mg/m3	
13463-67-7	TiO2	0.1-1		N.A	N.A		N.A
Titan Oxide			10mg/m3			15mg/m3	

This product does not contain any of the following substances as ingredients. And if it contains any impurities, it does not exceed any of the thresholds of RoHS.

Cadmium, Hexavalent Chromium, Mercury, Lead, Polybrominated biphenyls (PBB), Polybrominated diphenyleters (PBDE).

Hazardous Ingredients Information Chemical Name: Titan Oxide

**CAS Number** 13463-67-7 **EEC Number** : 236-675-5 OSHA Z-Tables (USA) 15mg/m3 ACGIH-TLV 10mg/m3 NTP (USA) IARC Monographs Group 2B Not listed Symbol (EU) Not listed R-Phrase (EU) Not listed DFG-MAK (GER) OELs-TWA (Australia): 10mg/m3 Not listed

California Proposition 65 (USA) : Not listed

> -1-[ANSI]

 $\label{eq:productName:PrintCartridgeYellowType MP C4500/C4540/LD445c MSDS Number: 841343 \\ Date Prepared: 07/09/2005 Date Modified: 2009/04/08 Date: 18/08/2009$ 



#### Section3: Hazards Identification

**Emergency Overview** 

**HMIS** Health: 1 Flammabilit: 1 Reactivity: 0 PPE:See section 8

Flammabilit: 1 **NFPA** Health: 1

Reactivity: 0

#### The Most Important Hazards

Adverse Human Health Effects:

There are no significant hazards expected with intended use.

#### Potential Health Effects

Primary Entry Routes:

Inhalation Yes Skin Yes Ingestion Yes **Environmental Effects:** 

There are no significant hazards expected with intended use.

Physical and Chemical Hazards:

There are no significant hazards expected with intended use.

Specific Hazards:

Dust explosion (like most finely grained organic powders)

Main Symptoms:

**Acute Inhalation Toxicity** 

Exposure to excessive amount of dust may cause physical irritation to respiratory tract.

Acute Oral Toxicity

Low acute toxicity in animal experiment.

Acute Eye Irritation

May cause slight transient irritation.

Acute Skin Irritation

May be non-irritant.

Sensitization

From test no apparent significant hazards are expected. (Only few cases reported on incidental allergy-related conjunctivitis or dermatitis.)

#### Chronic Effect

Slight pulmonary fibrosis has been reported in rats upon chronic inhalation exposure to a toner at 4mg/m3 every day for 2 years. No pulmonary change was found at 1mg/m3. These findings show that exposure to excessive amounts of powder may cause damage to lungs. However, normal use and handling of this product as intended, does not result in inhalation of excessive amounts of powder.

#### Carcinogenicity

Titanium dioxide contained in this product is classified to Group 2B of IARC as the result of inhalation test in use of rat.

But oral/skin test does not show carcinogenicity.

In the animal experiment with very high concentration of titanium dioxide (excessive burden of rat's lungs clearance mechanism (overload phenomenon)), the rat alone showed lung tumor. Under a normal use practice, the concentration should be far lower than the above; and it is assumed that there is no such use.

Also, relation between respiratory disease and work exposure of titanium dioxide is not observed with epidemiological survey.

Medical Conditions Aggravated by Exposure

Not applicable

Classification of the Chemical Product

This mixture is not classified as dangerous.

-2-[ANSI]  $\label{eq:productName:PrintCartridgeYellowType MP C4500/C4540/LD445c MSDS Number: 841343 \\ Date Prepared: 07/09/2005 Date Modified: 2009/04/08 Date: 18/08/2009$ 



## Section4: First Aid Measures

Inhalation:

Remove from exposure into fresh air and rinse mouth with water. Seek medical advice.

Skin Contact:

Wash thoroughly with soapy water.

Eye Contact:

Flush with a large amount of water until particles are removed. Seek medical advice.

Ingestion:

Drink several glasses of water to dilute ingested toner. Seek medical advice.

Immediate Medical Attention:

Immediate medical attention is not required.

### Section5: Fire Fighting Measures

Flash Point (degrees centigrade) : Not applicable : 0.223 or below Burning Rate (mm/sec) Autoignition Temperature (degrees : Not available

centigrade)

Flammable Limits % : LEL Not available **UEL Not available** 

Extinguishing Media to Avoid:

Not applicable. Specific Hazards:

Can form explosive dust-air mixtures when finely dispersed in air.

Fire-Fighting Instructions / Specific Method :

No special fire protecting method is required. Sprinkling or fire extinguishers can be used.

Protection of Firefighters:

Wear gloves, glasses, a mask if necessary.

### Section6: Accidental Release Measures

Personal Precautions:

Do not breathe in dust.

**Environment Precautions:** 

Do not flush into sewers or watercourses.

Methods for Cleaning Up:

Confirm there is no source of fire and if there is a source, remove it. Sweep up spilled powder slowly and clean remainder with wet cloth.

## Section7: Handling and Storage

Handling:

Technical Measures/Precautions

Not applicable

Safe Handling Advice

Do not handle in areas where there is wind or draught, this may cause dust to get into eyes.

Avoid breathing in dust.

Storage:

Technical Measures

Not applicable

Storage Conditions

Keep out of reach of children.

Store in dry, well-ventilated area, to maintain quality the temperature should not exceed 35degrees centigrade for a long time. Avoid direct sunlight.

Packaging material

Not applicable

Specific Use(s):

Image formation in printing machines or copiers.

-3-[ANSI]  $\label{eq:productName:PrintCartridgeYellowType MP C4500/C4540/LD445c MSDS Number: 841343 \\ Date Prepared: 07/09/2005 Date Modified: 2009/04/08 Date: 18/08/2009$ 



### Section8: Exposure Controls/Personal Protection

Technical measures:

Use adequate ventilation. None required with intended use.

**Control Parameters** 

Exposure Limit Value (I)

USA OSHA PEL (TWA) : 15mg/m3 (Total dust) 5.0mg/m3 (Respirable fraction) : 10mg/m3 (Inhalable fraction) ACGIH TLV (TWÀ) 3.0mg/m3 (Respirable fraction) 1.5mg/m3 (Respirable fraction) DFG MAK : 4.0mg/m3 (Total dust)

Personal Protection

Respiratory Protections (Specify Type)

None required in normal use. If the limit of exposure concentration is exceeded, use authorised

respirator. Eye Protection

Put on goggles if necessary.

Protective Gloves

Use vinyl or rubber gloves if necessary.

Protective Clothing or Equipment

Wear chemical-resistant apron or other impervious clothing if necessary.

Hygiene Measures

Wash hands after handling.

## Section9: Physical and Chemical Properties

Appearance

Physical state: Solid Form Powder Colour : Yellow

Odor : Slightly plastic odor : Not applicable pН

**Boiling Point (degrees** : Not applicable

centigrade)

Vapor Pressure (Pa) Not applicable

Vapor Density : Not applicable

(AIR=1)

Density (/3) : Approx. 1.2 Measuring Temp (degrees centigrade): 25

Formula Weight : Not applicable

Melting Point (degrees : (Softening point) Approx.110

centigrade)

Decomposition temperature (degrees : Not available

centigrade)

Viscosity (Pa s) : Not applicable Volatile (%) : 0.2 or below

Evaporation Rate (Butyl Acetate = 1): Not applicable Water Solubility (g/L) : Slightly soluble Chloroform Solubility (g/L) : Slightly soluble

### Section 10: Stability and Reactivity

Stability:

Stable

Hazardous Reaction:

Dust explosion, like most finely grained organic powders.

Condition to Avoid:

Not applicable in normal use.

Materials to Avoid:

Not applicable in normal use. Hazardous Polymerization:

None

Hazardous Decomposition or Byproducts:

Decomposition products will not occur.

[ANSI] -4Product Name : Print Cartridge Yellow Type MP C4500/C4540/LD445c MSDS Number : 841343 Date Prepared : 07/09/2005 Date Modified : 2009/04/08 Date : 18/08/2009



## Section11: Toxicological Information

**Acute Toxicity** 

Acute Oral Toxicity (LD50):

5000 or over

Acute Dermal Toxicity:

Not available

Acute Inhalation Toxicity:

Not available

Local effects

Acute Skin Irritation(PII):

1.0 or below (Rabbit) (None of hazardous situation will be caused under normal use condition.)

Acute Eye Irritation:

Slightly irritant (Based on other product test results of similar ingredients.)

Sensitization

Acute Allergenic Effects:

0 % (Marmot) (None skin sensitization.)

Specific Effects

Carcinogenicity

In 2008 IARC the re-evaluated Titanium dioxide as a Group 2B carcinogen for which there is inadequate human evidence, but sufficient animal evidence.

The latter is based upon the development of lung tumors in rats receiving chronic inhalation

exposures to Titanium dioxide at levels that induce particle overload of the lung. Use of this product, as intended, dose not result in inhalation of excessive dust.

Epidemiological study to date have not revealed any evidence of the relationbetween exposure to

titanium dioxide and diseases of the respiratory tract beyond general effects of dust.

Mutagenicity : Negative (Ames test)

Reproduction Toxicity: Does not contain substances listed as hazardous to reproductive health.

Teratogenic : Not available

## Section12: Ecological Information

Mobility No data are available on any adverse effects on the environment.

Persistence/Degradabilit : Not available

Bioaccumulation : Not available

**Ecotoxicity** 

Acute Toxicity for Fish (LC50) : Not classified as toxic (EU Directive 1999/45/EC)mg/l/96hr Acute Toxicity for Daphnia : Not classified as toxic (EU Directive 1999/45/EC)mg/l/48hr

Algae Inhibition Test (IC50) : Not classified as toxic (EU Directive 1999/45/EC)mg/l/72hr

> -5-[ANSI]

Product Name : Print Cartridge Yellow Type MP C4500/C4540/LD445c MSDS Number : 841343 Date Prepared : 07/09/2005 Date Modified : 2009/04/08 Date : 18/08/2009



### Section13: Disposal Consideration

#### General information:

Dispose of waste and residues in accordance with local authority requirements.

#### Disposal methods:

Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal. Confirm disposal procedures with local regulations.

#### Precautions

Do not throw the toner cartridge or toner into an open flame. Hot toner may scatter and cause burns or other damage.

### Section14: Transport Information

International Regulations

Land Transport

RID/ADR : Not applicable : Not applicable DOT 49 CFR ADNR : Not applicable

Sea Transport

**IMDG** Code : Not applicable

Air Transport

ICAO-TI/IATA-DGR : Not applicable **UN Number** : Not applicable

Specific Precautionary Transport Measures and Conditions

Avoid direct sunlight in quality.

## Section15: Regulatory Information

Regulations

**US** Information

Information on the label: Not required TSCA (Toxic Substances Control Act):

This toner complies with all applicable rules and regulations under TSCA.

SARA (Superfund Amendments and Reauthorization Act) Title III

313 Reportable Ingredients: Not regulated California Proposition 65: Not regulated

Canada Information

WHMIS Controlled product: Not a controlled product

**EU** Information

Information on the label (1999/45/EC and 67/548/EEC)

Symbol & Indication: Not required

R-Phrase: Not required S-Phrase: Not required

Special Precautions under 1999/45/EC Annex V: Not required

76/769/EEC

This product complies with applicable rules and regulations under 76/769/EEC

-6-[ANSI] Product Name: Print Cartridge Yellow Type MP C4500/C4540/LD445c MSDS Number: 841343

Date Prepared: 07/09/2005 Date Modified: 2009/04/08 Date: 18/08/2009



### Section16: Other Information

Explanation of Hazardous Materials Identification System [HMIS]& National Fire Protection Association [NFPA] Hazard Rating Systems:

Both the HMIS and NFPA systems use number from "0" to "4" to show the degree of hazard in an uncontrolled situation:

0=Minimum Hazard 1=Slight Hazard 2=Moderate Hazard 3=Serious Hazard 4=Severe Hazard Colors may also be used in both systems:

Blue=Health Hazard Red=Fire Hazard Yellow=Reactivity Hazard White=Indicate a special hazard HMIS will specify any Personal Protective Equipment reqired [PPE],

NFPA will specify OX(oxidizer), Acid(acid), ALK(Alkali), COR(Corrosive), W(use no water), xx(Radioactive).

Literature References:

ANSI Z400.1-1993

ISO 11014-1

Commission Directive 91/155/EEC

IARC (1996) "IARC Monograph on the Evaluation of the Carcinogenic Risk of Chemicals to Humans, Vol.65, Printing Process and Printing Inks, Carbon Black and Some Nitro Compounds", Lyon,

H.Muhle, B.Bellman, O.Creutzenberg, C.Dasenbrock, H.Emst, R.Kilpper, J.C.MacKenzie, P.Morrow, U.Mohr, S.Takenaka and R.Mermelstein(1991) "Pulmonary Response to Toner upon Chronic Inhalation Exposure in Rats" Fundamental and Applied Toxicology 17,pp280-299

IARC (2008) "IARC Monograph on the Evaluation of the Carcinogenic Risk of Chemicals to Humans, Vol.93'

NIOSH CURRENT INTELLIGENCE BULLETIN "Evaluation of Health Hazard and Recommendation for Occupational Exposure to Titanium Dioxide DRAFT"

: Threshold Limit Values for Chemical Substances and Physical Agents and **ACGIH-TLV** 

**Biological Exposure Indices** 

**OSHA Z-Tables** US Department of Labor, 29CFR Part 1910, Tables Z-1, Z-2, and Z-3 NTP (USA)

US Department of Health and Human Services National Toxicology

Program Annual Report on Carcinogens DFG-MAK GER: DFG List of MAK and BAT Value

: EU Directive 67/548/EEC Symbol (EC) 91/155/ EEĆ : EU Directive 91/155/ EEC 1999/45/EC Annex V : EU Directive 1999/45/EC 76/769/EEC EU Directive 76/769/EEC

EC 304/2003 Regulation (EC) No 304/2003 of the European Parliament and of the

Council of 28 January 2003 concerning the export and import of dangerous

WHMIS Controlled

product OELs-TWA (Australia) : Canada Workplace Hazardous Information System

Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:

3008 (1995)]

Abbreviations:

OSHA PEL PEL (Permissible Exposure Limit) under Occupational Safety and Health Act

**ACGIH-TLV** TLV (Threshold Limit Values) under American Conference of Governmental Industrial

**Hygienists** 

**DFG-MAK** MAK (Maximale Arbeitsplatz Konzentrationen) by Deutsche Forschungs Gemeinschaft **RoHS** Restriction of the use of certain Hazardous Substances in Electrical and Electronic

Equipment

**TWA** Time Weighted Average

**IARC** International Agency for Research on Cancer

NTP National Toxicology Program

**WHMIS** Workplace Hazardous Information System

NOHSC National Occupational Health and Safety Commission Act 1985

Disclaimer(S):

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Ricoh Americas Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Ricoh Americas Corporation assumes no legal responsibility for use or reliance upon this information.

-7-[ANSI]