

-----  
Section I. General Information  
-----

## MSDS Identifier Code

Supplier ID: Ricoh Product Code: 889275

Identity: Ricoh FT Toner Type 510 - Black

## Manufacturer's Name and Address:

Ricoh Corporation  
5 Dedrick Place  
West Caldwell, NJ 07006

Emergency Telephone Number: (800) 336-6737

Telephone Number for Information: (201) 882-2000, (800) 336-6737

Synonyms &amp; Common Names: Ricoh FT Toner Type 510 - Black

Uses: FT5733, FT5433, FT4427, FT4727

Chemical Formula: Mixture

## Registry numbers

CAS Number: 0-00-0

RTECS Number: N/App

Date Prepared: 04/25/92 Filed/Prepared By: RICOH CQA/EA Division

-----  
Section II. Hazardous Ingredients/Identity Information  
-----

## Composition

Component	%	CAS #	OSHA Pel	ACGIH TLV
*Polyester Resin (CASH Confidential)	26.00	0-00-0	N/App	N/App
*Styrene Acrylic Polymer	57.00	25036-19-5	N/App	N/App
Polyolefine	04.00	9003-07-0	N/App	N/App
Carbon Black	13.00	1333-86-4	3.5mg/m3	3.5mg/m3
*Non-hazardous	-	-	-	-
Polyolefine is listed on the IARC Monograph.	-	-	-	-
Carbon Black is listed on the IARC Monograph	-	-	-	-
and the Massachusetts Substance List.	-	-	-	-
The IARC has evaluated the evidence for the	-	-	-	-
carcinogenicity of Carbon Black and Polyole-	-	-	-	-
fine as inadequate to determine a carcino-	-	-	-	-
genic risk for humans.	-	-	-	-
THIS PRODUCT IS NON-HAZARDOUS	-	-	-	-
All components of this mixture comply	-	-	-	-
with the United States TSCA.	-	-	-	-

## Exposure Limits (TLV/PEL)

OSHA: See data above  
NIOSH: Not applicable  
ACGIH: See data above  
State: Not applicable  
Other: None

-----  
Section III. Physical/Chemical Characteristics  
-----

Boiling Point: Not applicable      Specific Gravity: 1.2g/cm3  
Vapor Pressure: Not applicable      % Volatile by Volume: Not applicable  
Melting Point: 80C or higher      Vapor Density (Air=1): Not applicable  
Evaporation Rate (n-BuAc=1): Not applicable

Solubility in Water: Less than 0.1%

Appearance and Odor: Black powder with slight plastic odor

-----  
Section IV. Fire and Explosion Hazard Data  
-----

Flash Point and Method: Not applicable

Explosive Limits: LEL N/App UEL N/App  
Comments: Not applicable

Extinguishing Media: CO2, dry chemicals, foam or water

Special Fire-Fighting Procedures: No special fire-fighting procedure is necessary.

Unusual Fire and Explosion Hazards: Airborne dispersal of most finely divided organic powders such as toner may form an explosive mixture. Do not incinerate loose or spilled toner.

-----  
Section V. Reactivity Data  
-----

Stability: Stable

Conditions to Avoid: Not applicable

Incompatibility (Materials to Avoid): Not applicable

Hazardous Decomposition or Byproducts: Carbon monoxide and other decomposition products in the case of incomplete combustion.

Hazardous Polymerization: Will not Occur  
Conditions to Avoid: Not applicable

---

Section VI. Health and Hazard Data

---

Routes of Entry: Eyes, inhalation, ingestion

Health Hazards of Short-Term exposure (Acute)

Eyes: May cause temporary eye discomfort.

Skin: No skin irritation

Inhalation: Gasping

Ingestion: Greater than 5g/kg bodyweight

Health Hazards of Long-Term exposure (Chronic): A Xerox sponsored chronic inhalation study in rats using a special test toner revealed there were no lung changes at all in the lowest exposure level (1mg/m<sup>3</sup>), the most relevant level to potential human exposures. A very slight degree of fibrosis was noted in 25% of the animals at the middle exposure level (4mg/m<sup>3</sup>) while a slight degree of fibrosis was observed at the highest exposure level (16mg/m<sup>3</sup>) in all animals. These findings are attributed to "Lung Overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. The special test toner was ten times more respirable than commercially available toner to comply with EPA testing protocol and would not function properly in Xerographic equipment.

Carcinogenicity: See Section II

NTP? No IARC Monographs? Yes OSHA Regulated? No

Signs and Symptoms of Exposure: Not applicable

Medical Conditions Generally Aggravated by Exposure: Not applicable

Emergency and First Aid Procedures

First Aid

Eyes: Try to remove with eye drops or flush with water. If unsuccessful, get medical attention.

Skin: Wash thoroughly with soap and water.

Inhalation: Remove from exposure.

Ingestion: Dilute stomach contents with several glasses of water.

Additional Information: Ames test result: Negative

---

Section VII. Precautions for Safe Handling and Use

---

Steps to be Taken in Case Material is Released or Spilled: If spilled, sweep up using an approved toner vacuum cleaner with a .5 micron filter or smaller such as the Atrix AAA Toner Vacuum (Ricoh EDP Code 342MIU). Use of a vacuum

cleaner not rated for toner particulate could be a potential fire hazard and/or result in personal injury.  
Remove residue with soap and water.

Waste Disposal Method: Used toner should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Do not incinerate loose or spilled toner. (See section IV). Disposal regulations vary from locality to locality, therefore, consult your local office of the EPA to determine proper method of disposal.

Precautions to Be Taken in Handling and Storing: Cleanse skin thoroughly after contact, before breaks and meals, and at the end of work periods. Keep out of reach of children.

Other Precautions: Not applicable

---

Section VIII. Control Measures

---

Respiratory Protection: None required under normal conditions of use.

Ventilation

Local Exhaust: None required under normal conditions of use.

Special: None

Mechanical (general): None required under normal conditions of use.

Other: None

Protective Gloves: None required under normal conditions of use.

Eye Protection: None required under normal conditions of use.

Other Protective Clothing or Equipment: None

Work and Hygienic Practices: Cleanse skin thoroughly after contact, before breaks and meals, and at the end of work periods.