MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Material name HP Color LaserJet CF365A Imaging Drum Cartridge

Version # 01

Issue date 08-Nov-2013

Product use This product is a magenta toner preparation that is used in HP Color LaserJet Enterprise flow MFF

M880 series printers.

Company identification Hewlett-Packard Company

3000 Hanover Street Palo Alto, CA 94304-1185

United States

Telephone 650-857-5020

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-760-710-0048 **HP Customer Care Line**

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. Hazards Identification

Potential health effects

Eyes May cause transient slight irritation Skin Unlikely to cause skin irritation.

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Use of

this product as intended does not result in inhalation of excessive amounts of dust.

Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

Other hazards This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, as amended. None of the ingredients have been classified as carcinogens according

to EU, IARC, MAK, NTP, OSHA or ACGIH.

3. Composition / Information on Ingredients

Non-hazardous components	CAS #	Percent
Styrene acrylate copolymer	Trade Secret	<85
Pigment	Trade Secret	<10
Wax	Trade Secret	<10
Amorphous silica	7631-86-9	<3

4. First Aid Measures

General advice No information

First aid procedures

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at

least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Inhalation Move person to fresh air immediately. If irritation persists, consult a physician.

Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

Material name: CF365A MSDS US 5. Fire Fighting Measures

Flammable properties Like most organic material in powder form, toner can form explosive dust-air mixtures when finely

dispersed in air.

Extinguishing media

Suitable extinguishing

media

CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

Fire fighting

equipment/instructions

If fire occurs in the printer, treat as an electrical fire.

Specific methods

None established.

Hazardous combustion

products

Carbon monoxide and carbon dioxide.

6. Accidental Release Measures

Personal precautions Minimize dust generation and accumulation.

Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a

damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust

explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with

federal, state, and local regulations.

7. Handling and Storage

Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from strong oxidizers.

Store at room temperature.

8. Exposure Controls / Personal Protection

Occupational exposure limits

US. NIOSH: Pocket Guide to Chemical Hazards

ComponentsTypeValueAmorphous silica (CASTWA6 mg/m37631-86-9)

Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10

mg/m3

Engineering controlsUse in a well ventilated area.

Personal protective equipment

General No personal respiratory protective equipment required under normal conditions of use.

9. Physical & Chemical Properties

AppearanceFine powderPhysical stateSolid.FormsolidColorMagenta

Odor Slight plastic odor
pH Not applicable
Vapor pressure Not applicable
Boiling point Not applicable
Melting point/Freezing point Not available.

Material name: CF365A MSDS US

13197 Version #: 01 Issue date: 08-Nov-2013

Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

Specific gravity 1 - 1.2

Flash point Not applicable **Viscosity** Not applicable **Percent volatile** 0 % estimated

176 - 266 °F (80 - 130 °C) Softening point

VOC Not available

Other information No information available

Other data

Decomposition > 392 °F (> 200 °C)

temperature

10. Chemical Stability & Reactivity Information

Chemical stability Stable under normal storage conditions. **Conditions to avoid** Imaging Drum: Exposure to light

Incompatible materials Strong oxidizers

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

Possibility of hazardous

reactions

Will not occur.

11. Toxicological Information

Toxicological data

Test Results Components Species

Amorphous silica (CAS 7631-86-9)

Acute

Oral

LD50 Mouse > 15000 mg/kg > 22500 mg/kg Rat

Sensitization Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA

HCS (US).

Chronic effects No information available.

Carcinogenicity Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulations

(USA), EU Directive, or Proposition 65 (California).

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Serious eye damage/eye

irritation

Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Test Results

Directive 67/548/EEC and as amended.

Mutagenicity Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Reproductive effects Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65,

and DFG (Germany).

Further information Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

12. Ecological Information

Ecotoxicological data Product

Species CF365A

LC50 Fish Fish > 100 mg/l, 96 Hours

LC50: > 100 mg/l, Fish, 96.00 Hours **Ecotoxicity**

Persistence and degradability Not available.

Material name: CF365A MSDS US

13197 Version #: 01 Issue date: 08-Nov-2013

13. Disposal Considerations

Disposal instructions

Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state,

and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.

14. Transport Information

Further information

Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

15. Regulatory Information

US federal regulations

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Not listed.

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Not regulated.

DEA Exempt Chemical Mixtures Code Number

Not regulated.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

SARA 311/312 Hazardous chemical No

No

Other regulations

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea,

New Zealand, and China.

State regulations

US. Massachusetts RTK - Substance List

Amorphous silica (CAS 7631-86-9)

US. Pennsylvania RTK - Hazardous Substances

Not regulated.

US. Rhode Island RTK

Not regulated.

16. Other Information

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Material name: CF365A MSDS US

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and

may not meet regulatory requirements in other countries.

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

Issue date 08-Nov-2013

Manufacturer information Hewlett-Packard Company

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value **TSCA** Toxic Substances Control Act

VOC Volatile Organic Compounds

Material name: CF365A

MSDS US

F / F