

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Identification of the

preparation

CN636Series

Product use Inkjet printing

Version # 06

Revision date 29-Sep-2011

Company identification Hewlett-Packard Company

3000 Hanover Street Palo Alto, CA 94304-1185

United States

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 HP Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. Hazards Identification

Emergency overview Contact with skin and eyes may result in irritation. Ingestion may result in nausea, vomiting and

diarrhea. May cause sensitization of susceptible persons.

Acute health effects

Any potential hazards are presumed to be due to exposure to the components.

Skin contact *2-pyrrolidone*

Contact with skin may result in irritation.

Alkyldiol

Contact with skin may result in irritation.

Polymer 683-K salt

Contact with skin may result in irritation.

Eye contact *2-pyrrolidone*

Contact with eyes may result in irritation.

Alkyldiol

Contact with eyes may result in irritation.

Polymer 683-K salt

Contact with eyes may result in irritation.

Inhalation *2-pyrrolidone*

Inhalation may result in respiratory irritation.

Alkyldiol

Inhalation may result in respiratory irritation.

Ingestion 2-pyrrolidone

Ingestion may result in nausea, vomiting and diarrhea.

Diethylene glycol

Harmful if swallowed. May cause kidney and liver damage. May depress the central nervous

system.

Polymer 683-K salt

Swallowing large amounts may cause digestive discomfort. Ingestion may result in nausea,

vomiting and diarrhea.

Material name: CN636Series MSDS US

9389 Version #: 06 Revision date: 29-Sep-2011 Print date: 29-Sep-2011

Potential health effects

Routes of exposure Potential routes of overexposure to this product are skin and eye contact

Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this

product under normal use conditions.

Complete toxicity data are not available for this specific formulation

Chronic health effects

None known.

Carcinogenicity

None of the components present in this formulation at concentrations equal to or greater than

0.1% are listed by EU, MAK, IARC, NTP or OSHA.

3. Composition / Information on Ingredients		
Components	CAS #	Percent
Water	7732-18-5	70 - 80
2-pyrrolidone	616-45-5	5 - 7.5
Diethylene glycol	111-46-6	5 - 7.5
Alkyldiol	Proprietary	2.5 - 5
Triethanolamine	102-71-6	< 1.5
Polymer 683-K salt		< 2.5

Composition comments

This ink supply contains an aqueous ink formulation.

This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard

Communication Standard).

4. First Aid Measures

First aid procedures

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at

least 15 minutes or until particles are removed. If irritation persists get medical attention.

Skin contact Wash affected areas thoroughly with mild soap and water. If irritation persists get medical

tention.

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Ingestion If material is ingested, immediately contact a physician or poison control center.

5. Fire Fighting Measures

Flammable properties

Combustion generates toxic fumes of fluoride/fluorine compounds; aldehydes, ketones, acetylene.

Extinguishing media

Suitable extinguishing

media

CO2, water, dry chemical, or foam

Unsuitable extinguishing

media

None known.

Specific methodsNone established. **Hazardous combustion**Refer to section 10.

products

6. Accidental Release Measures

Personal precautions

Wear appropriate personal protective equipment.

Environmental precautions

Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Other information

Soak up with inert absorbent material. Slowly vacuum or sweep the material into a bag or other sealed container. Dispose of in compliance with federal, state, and local regulations. See also section 13 Disposal considerations.

7. Handling and Storage

Handling

Avoid contact with skin, eyes and clothing.

Storage

Keep out of the reach of children. Keep away from excessive heat or cold. Store away from strong

Material name: CN636Series

9389 Version #: 06 Revision date: 29-Sep-2011 Print date: 29-Sep-2011 2 / 5

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH

Components Type Value

Triethanolamine (102-71-6) **TWA** 5.0000 mg/m3

U.S. - WEEL

Value Components **Type**

TWA 10.0000 mg/m3 Diethylene glycol (111-46-6)

Exposure limits have not been established for this product. **Exposure guidelines**

Engineering controls Use in a well ventilated area.

Personal protective equipment

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

General Use personal protective equipment to minimize exposure to skin and eye.

9. Physical & Chemical Properties

Appearance Not available.

Color Cyan

Not available. Odor **Odor threshold** Not available. **Physical state** Liquid

Form Not available.

9.4 pН

Melting point Not available. Freezing point Not available. **Boiling point** Not determined

Flash point > 200 °F (> 93.3 °C) Pensky-Martens Closed Cup

Evaporation rate Not determined Flammability limits in air, Not available. upper, % by volume

Flammability limits in air,

lower, % by volume

Not determined

Not determined Vapor pressure Not available. Vapor density Specific gravity 1 - 1.1

Not available. Relative density Solubility (water) Soluble in water **Auto-ignition temperature** Not determined Not available. **Decomposition temperature** VOC < 236 g/l

Other information VOC content (less water, less exempt compounds) = < 913 g/L (U.S. requirement, not for

emissions)

VOC data based on formulation (Organic compounds minus solids)

10. Chemical Stability & Reactivity Information

Chemical stability Stable under recommended storage conditions. **Incompatible materials** Incompatible with strong bases and oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. hydrogen fluoride, fluorinated hydrocarbons,

aldehydes, ketones

Material name: CN636Series MSDS US Possibility of hazardous reactions

Will not occur.

11. Toxicological Information

Serious eye damage/eye

irritation

Not available.

Further information This ink formulation has not been tested for toxicological effects.

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

12. Ecological Information

Aquatic toxicity LC50/96h/Fathead minnows =>750 mg/L

Persistence and degradability Not available.

13. Disposal Considerations

Disposal instructions

Dispose of in compliance with federal, state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your lessting, places visit better (hours) by com/recycle.

is available in your location, please visit http://www.hp.com/recycle.

14. Transport Information

Further information

Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

15. Regulatory Information

US TSCA 12(b): Does not contain listed chemicals.

CERCLA (Superfund) reportable quantity

None

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 Yes

hazardous chemical

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No Delayed Hazard - No

Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous

Yes

chemical

State regulations

US - Pennsylvania RTK - Hazardous Substances: Listed substance

2-pyrrolidone (CAS 616-45-5) Listed. Diethylene glycol (CAS 111-46-6) Listed.

Regulatory information

All chemical substances in this product are notified or exempt from notification under chemical substance notification laws in the following countries: Australia, Canada, European Union, Japan,

New Zealand, Switzerland, and USA..

16. Other Information

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

Material name: CN636Series MSDS US

HMIS® ratings Health: 1

Flammability: 2 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 2 Instability: 0

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and

may not meet regulatory requirements in other countries.

Issue date 29-Sep-2011

This data sheet contains changes from the previous version in section(s):

Product and Company Identification: Alternate Trade Names Composition / Information on Ingredients: Ingredients

Manufacturer information Hewlett-Packard Company

3000 Hanover Street

Palo Alto, California 94304-1112 US

(Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: CN636Series MSDS US

9389 Version #: 06 Revision date: 29-Sep-2011 Print date: 29-Sep-2011