Product Information Sheet

Article and Corporate Identification

Product: Epson Ink Cartridge T029201

for use with Epson Stylus Color C60

Printers

Manufacturer/Distributor: Epson America, Inc.


3840 Kilroy Airport Way

Long Beach, CA 90806

United States

TEL: 562-276-1369 FAX: 562-997-5799

Medical Emergency Number: (800) 859-1397



The EPSON T029201 Ink Cartridge Epson Quick-Dry ink is engineered to provide superior results.

2. **Composition Information**

This is an aqueous ink formulation

Ink Composition	CAS No.	% By Weight
Proprietary dyes and pigments	-	< 3 %
Diethylene glycol	111-46-6	< 10 %
Proprietary organic materials	-	15 – 20 %
Glycerols	-	10 - 15 %
Water	7732-18-5	balance

Hazard Identification

3.1 Emergency Overview: Ink component is a three part light yellow, magenta, and cyan liquid that may cause eye

irritation. Avoid contact with eyes or clothing. In the case of skin contact, wash with soap

and water. Keep out of reach of children.

3.2 Potential Health Effects:

Ink contact with eye may be mildly irritating. See Section 11 for Toxicology. Eves:

Ink contact with skin may cause irritation, swelling, or redness. It is not expected to cause an allergic

skin reaction. See Section 11 for Toxicology.

Inhalation: Intentional exposure to ink vapors may cause respiratory irritation. See Section 11 for Toxicology.

May cause upset stomach. See Section 11 for Toxicology. Ingestion:

Skin:

4. First Aid Measures

4.1 Eyes: Immediately flush with room temperature, low pressure, clean water for at least 15 minutes. Seek

medical attention if eye irritation continues.

4.2 Skin: Wash surface areas with soap and water. Wash soiled clothing before rewearing. Consult a physician

if irritation continues.

4.3 Inhalation: Remove subject to ventilated fresh air. Consult physician if necessary.

4.4 Ingestion: Seek medical advise; and attention if stomach continues to be upset.

5. Fire Fighting Measures

5.1 Flammability: Flash point is greater than 230 deg. F / 110 deg. C (closed cup in accordance with

ASTM D3278)

5.2 Extinguishing Media: Dry chemical or carbon dioxide

5.3 Fire Fighting Instructions: No special fire fighting procedures are required other than breathing apparatus. No

special explosion hazards are known.

6. Accidental Release Measures

If a spill occurs, use sponges to wipe-up ink, then rinse area with damp cloth. Place waste in closed container for disposal. Use proper ventilation. Do not dispose of waste to the sewer. No eye or skin protection required during clean-up. Wash hands with soap and water.

7. Precautions for Safe Handling and Use

Keep out of reach of children and do not drink ink. Do not store the cartridge in high or freezing temperatures. Keep cartridge out of direct sunlight. Do not dismantle cartridge. Do not store cartridges with oxidizing agents or explosives. Make sure cartridge is dry before insertion into printer housing.

8. Exposure Controls and Personal Protection

8.1 Engineering Controls: None required

8.2 Exposure Controls: None required

8.3 Personal Protection: None required when cartridges are used as intended

9. Physical and Chemical Properties of Ink Formulation

Appearance: Yellow, Magenta, and Cyan Liquid

Odor: None *pH:* 9 - 10

Boiling point: Approximately 212 deg. F / 100 deg. C

Freezing point: Less than 32 deg. F / 0 deg. C

Melting point: Less than 32 deg. F / 0 deg. C

Flash point: Greater than 230 deg. F / 110 deg. C (closed cup, ASTM D3278)

Autoflammability: None

Explosive properties:

None

Oxidizing properties:

None

Vapor density:

Greater than 1 (air = 1) 1.06 ~ 1.08at 68 deg. F / 20 deg. C

Relative density:

Complete

Solubility in water: Solubility in fat:

No data available

Partition coefficient:

No data available

Viscosity:

Less than 5 mPa-s

10. Stability and Reactivity

Stability:

Stable

Hazardous polymerization:

Will not occur

Hazardous decomposition products:

None

Incompatible materials:

Oxidizers and explosives

11. Toxicology and Health Hazards

Routes Of Overexposure: Eye, skin, inhalation, and oral

Acute Health Hazards:

- Overexposure of eye surface to ink may be mildly irritating
- Overexposure of skin to ink contact may cause irritation and in some people swelling and redness
- Intentional inhalation overexposure to ink vapors may result in respiratory tract irritation
- Intentional or accidental oral ingestion may cause an upset stomach

Chronic Health Hazards: None known

Carcinogenicity:

None Known

Toxicity Data:

Oral LD50

Dermal LD50

Inhalant LC50

OSHA Regulated?

> 5000mg/kg(Rats)

> 2000mg/kg(Rats)

Not Applicable

Not Established

12. Ecological Information

No data available on the adverse effects of this material on the environment

13. Disposal Considerations

Used and unused cartridges are not a federal RCRA hazardous waste. Disposal should be in accordance with federal, state, and local requirements.

14. Transportation Information

Not regulated as a Hazardous Material by DOT, IMO, or IATA.

This material does not require a TSCA Section 12(b) Export Notification.

15. Regulatory Considerations

U.S. DOT Hazard Class Regulated?

NO

U.S. OSHA Inhalation Hazard?

NO

In U.S., NFPA/HMIS Hazard Rating:

Health (1), Flammability (1), Instability/Reactivity (0), Other (0)

16. Other Information

This is a revised Product Information Sheet which replaces all prior U.S. Information and Data Sheets for this product.

This "Product Information Sheet" contains health, safety, and environmental information. It does not replace any precautionary language or use and disposal information which accompanies the product. The information contained herein is believed to be accurate at the time of preparation, but should only be used as a guide. It is subject to revision from time to time. EPSON does not warrant the completeness or accuracy of the information contained herein.

In consideration of our environment and world neighbors, all genuine EPSON ink cartridges are engineered and based on an "Ecologically Friendly" water based technology. EPSON ink cartridges contain no CFCs or harsh liquid solvents.

"Wait until you see it in EPSON COUR"