

Tel. No. (540) 949-1000

Emergency No. (303) 370-9238 Email: MSDS@tallygenicom.com Fax. No. (540) 949-1612

Material Safety Data Sheet

Complies with OSHA Hazard Communications Standard 29 CFR 1910.1200

Part Numbers Covered with this MSDS

080294	080296	082727	083683
082725	086039	086041	086043
	082285	085014	

Section I Material Identification

MSDS Number:	R76	Date:	7/31/01
Product Code:	15-0120K	Supercedes:	
Trade Name:	Black Inked Matrix Fabric Ribbon (Cartridge / Spool)		

Section II Hazardous Ingredients

<u>Name</u>	CAS No.	% by Weight
Mineral Oil	64742-52-5	5 mg/cu m as oil mist
Carbon Black	1333-86-4	3.5 mg/cu m
No reportable quantities	s of other hazardous	ingredients are present.

MSDS R76 1 of 4



Tel. No. (540) 949-1000

Emergency No. (303) 370-9238 Email: MSDS@tallygenicom.com Fax. No. (540) 949-1612

Material Safety Data Sheet

Complies with OSHA Hazard Communications Standard 29 CFR 1910.1200

MSDS Number: R76

Section III Physical Data

Boiling Point:	Not Applicable	Solubility in Water:	Not Applicable
Evaporation Rate:	Not Applicable	Vapor Density:	Not Applicable
Melting Point:	Not Applicable	Vapor Pressure:	Not Applicable
Specific Gravity:	Not Applicable	Volume % volatile:	Not Applicable
Appearance and Od	or: Plastic housing	with black inked ribbon, slightly pungent	
	odor.		

Section IV Fire and Explosion Hazard Data

Flash Point:	> 300° F			Flammable Limits:	Not Known
Extinguishing	g Media: Foam, C		CO ₂ , Dry Chemical		
Special Firefighting Procedures:		Treat as an oil fire. Use self contained breathing			
		apparatus when exposed to fume.			
Unusual Fire and Explosion Hazards:		ds:	No unusual hazaro	ds	

Section V Reactivity Data

Stability:	Stable	Conditions to Avoid:	Temperature above 190° F	
Incompatibility (materials to avoid):		s to avoid):	Strong chemical oxidizing agents	
Hazardous Decomposition or Byproducts:			Not expected	
Hazardous Polymerization:			Will not occur	

MSDS R76 2 of 4



Tel. No. (540) 949-1000

Emergency No. (303) 370-9238 Email: MSDS@tallygenicom.com Fax. No. (540) 949-1612

Material Safety Data Sheet

Complies with OSHA Hazard Communications Standard 29 CFR 1910.1200

MSDS Number: R76

Section VI Health Hazard Data

Threshold Limit Value:	Not Applicable		
Effects of Overexposure:	Not Applicable		
Emergency and First Aid Procedures:	Not Applicable		

Section VII Precautions for Safe Handling and Use

Steps to be taken in case material is released or spilled:

Clean up spills promptly to prevent accidents.

Waste Disposal Method:

Discard as normal waste in accordance to Local, State and Federal regulations.

Precautions to be taken in handling and storing:

Do not store near high heat or open flame. Do not expose to strong acids, bases, and oxidizers.

Other Precautions:

Provide lanolin based hand cleaner to avoid frequent harsh washing of skin with strong soap. Store in a cool dry place.

Section VIII Control Measures

Respiratory Protection:		None Required			
Ventilation:	ntion: Not Applicable		Eye Protection: Not Applicable		Not Applicable
Protective Gloves, Clothing or Equipment:		ment:		None Required	

MSDS R76 3 of 4



Tel. No. (540) 949-1000

Emergency No. (303) 370-9238 Email: MSDS@tallygenicom.com Fax. No. (540) 949-1612

Material Safety Data Sheet

Complies with OSHA Hazard Communications Standard 29 CFR 1910.1200

MSDS Number: R76

Section IX Regulatory Information

This product contains no levels of listed substances, which the State of California (Proposition 65), has found cancer, birth defects, or other reproductive harm, which would require a warning under the statute.

No toxic chemicals subject to the reporting requirements of Section 313 of Title III and of 40 CFR Section 372 are present in this product

TallyGenicom believes the information contained herein is current as of the date of the Material Safety and Data Sheet. The information is provided in good faith and is accurate to the best of our knowledge. No warranty expressed or implied is given. This information is offered solely for your consideration and verification. Users must make independent determination of suitability and conditions of safe use of this product.

MSDS R76 4 of 4