

Lanier Worldwide Inc. 2300 Parklake Drive, NE Atlanta, GA USA 30345-2979

# MATERIAL SAFETY DATA SHEET

Emergency Telephone: 800-551-3087

Section 1: Chemical Product and Company Information

Identity: Product ID: Black Toner Type 1130D

480-0198

Synonyms & Common

Black Toner Cartridge, Type 1130D

Names:

Uses:

Lanier LD115, LD118, LD118d, LD116, LD120, LD120d

Chemical Formula:

Mixture

MSDS No. **CP-407** 

10/31/2005 Issued: Supersedes: 01/19/2004

Date: 10/31/2005 Prepared by:

Contact:

EH&S Department 770-496-9500 Approved by: Larry Choskey, Manager, CEH&S Walter Fricke, Manager, Safety & European

Environment.

Lanier Worldwide, Inc.

Im Taubental D-41468 Neuss, Germany +49-2131-387-177

Section 2: Composition / information on ingredients				
Polyester resin Carbon black	PERCENT > 80 < 15	CAS No. Confidential 1333-86-4	EXPOSURE LIMITS  Not listed  3.5 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup>	SOURCE N/a OSHA TWA ACGIH TWA
Carnauba wax	< 10	8015-86-9	Not listed	N/a

\*PEL as the product: 15mg/m³ (total dust), 5mg/m³ (respirable dust) \*TLV as the product: 10mg/m³ (total dust), 5mg/m³ (respirable dust)

Section 3: Hazards Identification

**HMIS Rating:** 

FLAMMABILITY = 1 REACTIVITY = 0

HEALTH = 1 SPECIAL = none

Health Hazards (Acute, Chronic, Immediate and Potential): Minimum irritation to respiratory tract may occur as with exposure to any non-toxic dust. May cause gasping if inhaled. Inhalation should be avoided. May cause temporary eye discomfort. Health Hazards of Long Term exposure (Chronic): Prolonged inhalation of excessive dust may cause lung damage. It is attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. Use of this product, as intended, does not result in inhalation of excessive dust.

Carcinogenicity: Carbon Black was reclassified as a Group 2B by the IARC in 1996 based upon the result of only the inhalation

study in rats. However, there was not observed the incidence of tumors on the test results on dermal or oral studies. Also, 2-years inhalation study using a typical toner containing carbon black showed no association between toner exposure and animal tumors.

Section 4: First Aid Measures

Inhalation:

Gargle with water. Remove to fresh air if effects

occur. Get medical attention if needed.

**Eye Contact:** 

In case of contact, immediately flush eyes with water for 15 minutes. Get medical

attention if needed.

**Skin Contact:** 

Wash with soap and water.

Ingestion:

Dilute stomach contents with several glasses of water. Get medical attention.

Section 5: Fire Fighting Measures

Suitable extinguishing media: CO<sub>2</sub>, dry chemical, foam or water.

Extinguishing media which may not be used for safety reasons: none

Special protective equipment for fire fighters: none

UEL: n/a

Page 2 of 3

CP-407

# Section 6: Accidental Release Measures

Spill / leak Procedures: If spilled, sweep up using an approved toner vacuum with a 0.5 micron filter or smaller, such as the Atrix AAA Toner Vacuum or 3M Toner Vacuum. Use of a vacuum cleaner not rated for toner particles, could result in a fire or personal injury. Remove residue with soap and cold water.

Miscellaneous: Keep product out of sewers and watercourses.

Personal protection: Avoid inhalation of dust.

### Section 7: Handling and Storage

Special Handling:

Cleanse skin after contact before breaks or meals, and end of workday.

Do not handle in areas where the wind blows.

Special Storage:

Minimize the breathing of dust Avoid direct sunlight. Keep out of reach of children. Store in a cool, dry place. Below 35C (95F)

# Section 8: Exposure Control and Personal Protection Information:

Respiratory Protection: none required under normal use.

Hand Protection: none required under normal use.

Eye Protection: none required under normal use.

Skin Protection: none required under normal use.

## Section 9: Physical and Chemical Properties

CHARACTERISTICS:

Appearance:

Form: Odor

Solubility in Water: Specific gravity: Density:

Insoluble N/a 1.2 g/cm3

Slight plastic odor

Black

Powder

Melting point: Vapor pressure: Vapor density:

Evaporation rate: Boiling point:

110°C N/a N/a

N/a N/a

## Section 10: Stability and Reactivity

Conditions to avoid:

Hazardous decomposition products:

None

Will not occur

Materials to avoid: None Stability: Stable

## Section 11: Toxicological Information:

Ames test: Negative

Acute skin irritation: Acute allergenic effects: no data

no data

Acute oral toxicity: (Rat): > 5000mg/kg

Acute allergenic effects: no data

Special effects: Carcinogenicity: In 1996 the IARC reclassified Carbon Black as a Group 2B carcinogen (possible human carcinogen). This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence. The latter is based upon the development of lung tumors in rats receiving chronic inhalation exposures to free carbon black at levels that induce particle overload of the lung. Studies performed in animal models other than rats have not demonstrated an association between carbon black and lung tumors. Moreover, 2-years cancer bioassay using a typical toner preparation containing carbon black did not demonstrate an association between toner exposure and tumor development in rats.

#### Section 12: Environmental / Ecological Information

Acute toxicity to fish: Persistence/Degradability: Algae inhibition test:

Not available Not known Not available Bioaccumulation:

Not known in bioaccumulation

Acute toxicity to daphnia: Not available

### Section 13: Disposal Consideration

Used toner should be disposed of under conditions that meet all federal, state and local environmental regulations. Disposal regulations vary from locality to locality; therefore consult your local Lanier office or the EPA to determine the proper method for disposal. Do not incinerate loose or spilled toner.