

### MATERIAL SAFETY DATA SHEET

# 1. Product and Company Identification

Identification of the

preparation

HP LaserJet C4182X-XC Print Cartridge

**Product use** This product is a toner preparation that is used in HP LaserJet

8100/8100mfp/8150/8150mfp/Mopier 320 series printers.

Version # 12

30-Jun-2010 **Revision date** 

Company identification **Hewlett-Packard Company** 

> 3000 Hanover Street Palo Alto, CA 94304-1185

**United States** 

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 HP Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

# 2. Hazards Identification

Acute health effects

Skin contact Unlikely to cause skin irritation. **Eve contact** May cause transient slight irritation

Inhalation Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Ingestion Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.

**Potential health effects** 

Potential routes of exposure under normal use conditions are skin, eye contact and inhalation. **Routes of exposure** 

Ingestion is not expected to be a primary route of exposure for this product under normal use

conditions.

Chronic health effects Prolonged inhalation of excessive amounts of any dust may cause lung damage. Use of this

product as intended does not result in inhalation of excessive amounts of dust.

Carcinogenicity None of the ingredients have been classified as carcinogens according to EU, IARC, MAK, NTP,

OSHA or ACGIH.

Other information This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive

1999/45/EC, as amended.

This preparation contains no component classified as Persistent, Bioaccumulative, and Toxic (PBT) or very Persistent and very Bioaccumulative (vPvB) as defined under Regulation (EC)

1907/2006.

# 3. Composition / Information on Ingredients

Components	CAS #	Percent
Iron oxide	1317-61-9	< 50
Styrene acrylate copolymer	Trade Secret	< 50

### 4. First Aid Measures

### First aid procedures

Eye contact Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at

least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Material name: C4182X-XC MSDS US 1/5 **Skin contact** Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

**Inhalation** Move person to fresh air immediately. If irritation persists, consult a physician.

**Ingestion** Rinse mouth with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

5. Fire Fighting Measures

**Flammable properties**Like most organic material in powder form, toner can form explosive dust-air mixtures when finely

dispersed in air.

**Extinguishing media** 

Suitable extinguishing

media

CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

**Protection of firefighters** 

Protective equipment and precautions for firefighters

If fire occurs in the printer, treat as an electrical fire.

**Specific methods** None established.

**Hazardous combustion** 

products

Carbon monoxide and carbon dioxide.

## 6. Accidental Release Measures

**Personal precautions** Minimize dust generation and accumulation.

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

**Other information** Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a

damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust

explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with

federal, state, and local regulations.

### 7. Handling and Storage

**Handling** Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use

with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

**Storage** Keep out of the reach of children. Store at room temperature. Store away from strong oxidizers.

Keep tightly closed and dry.

### 8. Exposure Controls / Personal Protection

**Exposure guidelines** USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

**Engineering controls** Use in a well ventilated area.

**Personal protective equipment** 

**General** No personal respiratory protective equipment required under normal conditions of use.

# 9. Physical & Chemical Properties

AppearanceFine powderColorNot available.OdorSlight plastic odorOdor thresholdNot available.Physical stateLiquidFormsolid

pH Not applicable
 Melting point Not available.
 Freezing point Not available.
 Boiling point Not applicable

Material name: C4182X-XC MSDS US

8932 Version #: 12 Revision date: 30-Jun-2010 Print date: 30-Jun-2010

Flash point Not applicable
Evaporation rate Not available.
Flammability limits in air, Not available.

upper, % by volume

Flammability limits in air, lower, % by volume

Not flammable

Vapor pressureNot applicableVapor densityNot available.Specific gravity1.5 (H2O = 1)Relative densityNot available.

**Solubility (water)** Negligible in water. Partially soluble in toluene and xylene.

Auto-ignition temperatureNot applicableDecomposition temperatureNot available.Softening point212 °F (100 °C)ViscosityNot applicableVOCNot available.

**Other information** Decomposition temperature: > 200 °C

# 10. Chemical Stability & Reactivity Information

Chemical stabilityStable under normal storage conditions.Conditions to avoidImaging Drum: Exposure to light

**Incompatible materials** Strong oxidizers

**Hazardous decomposition** 

products

Carbon monoxide and carbon dioxide.

Possibility of hazardous

reactions

Will not occur.

# 11. Toxicological Information

**Oral toxicity** LD50/oral/rat >2000 mg/kg; Not harmful. (OECD 401). Not classified for acute oral toxicity

according to EU Directive 67/548/EEC and 1999/45/EC.

Carcinogenicity Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA

Regulations (USA), EU Directive, or Proposition 65 (California).

**Inhalation toxicity** LC50: inh/rat 5 mg/l/4 hrs., (OECD 403).

Not classified for acute inhalation toxicity according to EU Directive 67/548/EEC and

1999/45/EC.

Serious eye damage/eye

irritation

Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

**Skin sensitization** Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU

Directive 67/548/EEC and as amended.

**Chronic toxicity** No information available.

**Sensitization** Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA

HCS (US).

**Mutagenicity** Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

**Reproductivity** Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65,

and DFG (Germany).

**Further information** Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

### 12. Ecological Information

**Ecotoxicity** LL50: 1000 mg/l, Rainbow Trout, 96.00 Hours

Persistence and degradability Not available.

Material name: C4182X-XC

# 13. Disposal Considerations

#### **Disposal instructions**

Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.

# 14. Transport Information

#### **Further information**

9 or more of these cartridges shipped together in a single package (e.g., box, container), by air, are regulated as a magnetized material. These requirements do not apply to single or dual pack cartridges contained in an original HP package and shrink wrapped on a pallet for shipment by air.

#### DOT

Not regulated as dangerous goods.

#### **IATA**

**Basic shipping requirements:** 

Proper shipping name UN number

Magnetized Material

2807

#### **IMDG**

Not regulated as dangerous goods.

#### **RID**

Not regulated as dangerous goods.

# 15. Regulatory Information

**US federal regulations** 

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA.

#### **CERCLA (Superfund) reportable quantity**

None

### Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical

No

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely

No

hazardous substance Section 311 hazardous

chemical

No

### **Regulatory information**

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.

# 16. Other Information

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

**HMIS**® ratings Health: 1

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Material name: C4182X-XC

8932 Version #: 12 Revision date: 30-Jun-2010 Print date: 30-Jun-2010

#### **Disclaimer** This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and

may not meet regulatory requirements in other countries.

**Issue date** 30-Jun-2010

This data sheet contains changes from the previous version in section(s):

11. Toxicological Information: Further information

Transport Information: Agency Name and Packaging Type/Transport Mode Selection

14. Transport Information: Further information

**Manufacturer information Hewlett-Packard Company** 

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

#### **Explanation of abbreviations**

**ACGIH** American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

**CERCLA** Comprehensive Environmental Response Compensation and Liability Act

**CFR** Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

**EPCRA** Emergency Planning and Community Right-to-Know Act (aka SARA)

**IARC** International Agency for Research on Cancer

**NIOSH** National Institute for Occupational Safety and Health

NTP National Toxicology Program

**OSHA** Occupational Safety and Health Administration

**PEL** Permissible Exposure Limit

**RCRA** Resource Conservation and Recovery Act

**REC** Recommended

**REL** Recommended Exposure Limit

**SARA** Superfund Amendments and Reauthorization Act of 1986

**STEL** Short-Term Exposure Limit

**TCLP** Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

**TSCA** Toxic Substances Control Act VOC Volatile Organic Compounds

Material name: C4182X-XC MSDS US 5/5

8932 Version #: 12 Revision date: 30-Jun-2010 Print date: 30-Jun-2010