

### 1. Product and Company Identification

Material name C9455A
Use of the preparation Inkjet printing

Version # 03

Revision date 01-Dec-2009

Company identification Hewlett-Packard Company

3000 Hanover Street Palo Alto, CA 94304-1185

**United States** 

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 HP Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

Date prepared Nov 30, 2009 MSDS number 592106

#### 2. Hazards Identification

Emergency overview Contact with skin and eyes may result in irritation. Ingestion may result in nausea, vomiting

and diarrhea.

Acute health effects

Any potential hazards are presumed to be due to exposure to the components.

Skin contact 2-pyrrolidone

Contact with skin may result in irritation.

Alkyldiol

Contact with skin may result in irritation.

Polymer 683-K salt

Contact with skin may result in irritation.

Eye contact 2-pyrrolidone

Contact with eyes may result in irritation.

Alkyldiol

Contact with eyes may result in irritation.

Polymer 683-K salt

Contact with eyes may result in irritation.

Inhalation 2-pyrrolidone

Inhalation may result in respiratory irritation.

Alkyldiol

Inhalation may result in respiratory irritation.

**Ingestion** 2-pyrrolidone

Ingestion may result in nausea, vomiting and diarrhea.

Diethylene glycol

Harmful if swallowed. May cause kidney and liver damage. May depress the central nervous

system.

Polymer 683-K salt

Swallowing large amounts may cause digestive discomfort. Ingestion may result in nausea,

vomiting and diarrhea.



Potential health effects

Routes of exposure Potential routes of overexposure to this product are skin and eye contact

Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this

product under normal use conditions.

Complete toxicity data are not available for this specific formulation

Chronic health effects

None known.

None of the components present in this formulation at concentrations equal to or greater than Carcinogenicity

0.1% are listed by EU, MAK, IARC, NTP or OSHA.

### 3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight
Water	7732-18-5	< 80
2-pyrrolidone	616-45-5	< 7.5
Alkyldiol	Proprietary	< 7.5
Diethylene glycol	111-46-6	< 2.5
Polymer 683-K salt		< 2.5
Composition comments	This ink supply contains an aqueous ink formulation.  This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard	

### 4. First Aid Measures

First aid procedures

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for Eye contact

at least 15 minutes or until particles are removed. If irritation persists get medical attention.

Skin contact Wash affected areas thoroughly with mild soap and water. If irritation persists get medical

attention.

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Communication Standard).

If material is ingested, immediately contact a physician or poison control center. Ingestion

### 5. Fire Fighting Measures

Flash point and method > 200 °F (> 93.3 °C); Pensky-Martens Closed Cup

**Hazardous combustion** 

products

Refer to section 10.

Flammable properties Combustion generates toxic fumes of fluorides/ fluorine compounds; aldehydes; ketones;

potential for acetylene.

**Extinguishing media** 

Suitable extinguishing

media

CO2, water, dry chemical, or foam

Unsuitable extinguishing

media

Unusual fire and explosion

None known.

hazard

Combustion generates toxic fumes of fluorides/ fluorine compounds; aldehydes; ketones;

potential for acetylene.

Special firefighting procedures None established.

### 6. Accidental Release Measures

Personal precautions Wear appropriate personal protective equipment.

**Environmental precautions** 

Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Other information

Soak up with inert absorbent material. Slowly vacuum or sweep the material into a bag or other sealed container. Use personal protective equipment to minimize exposure to skin and

eye. See also section 13 Disposal considerations.

Material name C9455A MSDS US Creation date Apr 30, 2003 Version number 3 2/5



7. Handling and Storage

Handling Avoid contact with skin, eyes and clothing.

Keep out of the reach of children. Keep away from excessive heat or cold. Store away from Storage

strong oxidizers.

8. Exposure Controls / Personal Protection

**Exposure guidelines** Exposure limits have not been established for this product.

Personal protective equipment

General Use personal protective equipment to minimize exposure to skin and eye.

Eye / face protection Not required under intended use.

Skin protection Protected gloves not required under intended use.

For use other than intended use (such as in the event of a large spill), goggles and respirators Respiratory protection

may be required.

General hygeine considerations

Handle in accordance with good industrial hygiene and safety practice.

### 9. Physical & Chemical Properties

Color Light Magenta **Odor threshold** Not available. **Physical state** Not available.

9.2 рΗ

Not available. Melting point Not available. Freezing point **Boiling point** Not determined

> 200 °F (> 93.3 °C); Pensky-Martens Closed Cup Flash point

**Evaporation rate** Not determined **Flammability** Not available. Not available. Flammability limits in air, upper, % by volume

Flammability limits in air,

lower, % by volume

Not determined

Not determined Vapor pressure > 1 (air=1.0) Vapor density 1 - 1.1Specific gravity

Not available. Relative density Solubility (water) Soluble in water Partition coefficient Not available.

(n-octanol/water)

Not determined **Auto-ignition temperature** Not available. **Decomposition temperature** 

#### 10. Chemical Stability & Reactivity Information

Chemical stability Stable under recommended storage conditions. Incompatible with strong bases and oxidizing agents. Incompatible materials

Hazardous decomposition

products

Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. aldehydes, ketones, hydrogen

fluoride, fluorinated hydrocarbons

Possibility of hazardous

reactions

Will not occur.

Material name C9455A MSDS US Creation date Apr 30, 2003 Version number 3 3/5



### 11. Toxicological Information

Not available.

12. Ecological Information

LC50/96h/Fathead minnows => 750 mg/L **Aquatic toxicity** 

Persistence and degradability Not available.

13. Disposal Considerations

**Disposal instructions** Dispose of in compliance with federal, state, and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine

if this service is available in your location, please visit http://www.hp.com/recycle.

### 14. Transport Information

**IATA** 

Proper shipping name Not applicable **Hazard class** Not applicable

**UN** number None **Packing group** N/A Packaging exceptions None

General Not a dangerous good under United States DOT, IATA, ADR, IMDG, or RID.

15. Regulatory Information

**US federal regulations** US TSCA 12(b): Does not contain listed chemicals.

**CERCLA (Superfund) reportable quantity** 

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No **Hazard categories** 

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous

Yes

International regulations

chemical

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South

Korea, New Zealand, and China.

State regulations

US - Pennsylvania RTK - Hazardous Substances: Listed substance

2-pyrrolidone (616-45-5) Listed. Diethylene glycol (111-46-6) Listed.

16. Other Information

**HMIS®** ratings Health: 1 Flammability: 2

Physical hazard: 0

Health: 1 NFPA ratings

Flammability: 2 Instability: 0

Material name C9455A MSDS US Creation date Apr 30, 2003 Version number 3 4/5



Issue date Nov 30 2009 7:05PM

Revision 3

Replaces sheet dated Nov 20 2009 6:19PM

Manufacturer information Hewlett-Packard Company

1000 NE Circle Boulevard Corvallis, OR 97330-4239 US (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation

(29 CFR 1910.1200).

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

MSDS sections updated 8. Exposure Controls / Personal Protection: Respiratory protection

8. Exposure Controls / Personal Protection: Eye / face protection

8. Exposure Controls / Personal Protection: Skin protection

14. Transport Information: General

#### **Explanation of abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

**CFR** Code of Federal Regulations

COC Cleveland Open Cup

**DOT** Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

**REC** Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act VOC Volatile Organic Compounds

Material name C9455A

Creation date Apr 30, 2003

Version number 3

MSDS US

5 / 5