

MATERIAL SAFETY DATA SHEET

| 1. Product and Company I | Identification | | | |
|---------------------------|---|--|--|--|
| Material name | HP Color LaserJet CF352A Yellow Print Cartridge | | | |
| Version # | 01 | | | |
| Issue date | 08-Nov-2013 | | | |
| Product use | This product is a yellow toner preparation that is used in HP Color LaserJet Pro MFP M176/ HF Color LaserJet Pro MFP M177 series printers. | | | |
| Company identification | Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-5020 Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-760-710-0048 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomer.inquiries@hp.com | | | |
| 2. Hazards Identification | | | | |
| Potential health effects | | | | |
| Eyes | May cause transient slight irritation | | | |
| Skin | Unlikely to cause skin irritation. | | | |
| Inhalation | Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. Use of this product as intended does not result in inhalation of excessive amounts of dust. | | | |
| Ingestion | Low acute toxicity. Ingestion is a minor route of entry for intended use of this product. | | | |
| Other hazards | This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive 1999/45/EC, as amended. | | | |

3. Composition / Information on Ingredients

| Hazardous components | CAS # | Percent |
|----------------------------|--------------|---------|
| Titanium dioxide | 13463-67-7 | <1 |
| Non-hazardous components | CAS # | Percent |
| Styrene acrylate copolymer | Trade Secret | <85 |
| Wax | Trade Secret | <10 |
| Pigment | Trade Secret | <5 |
| Amorphous silica | 7631-86-9 | <3 |

| 4. First Aid Measures | |
|-----------------------|--|
| General advice | No information |
| First aid procedures | |
| Eye contact | Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician. |
| Skin contact | Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists. |
| Inhalation | Move person to fresh air immediately. If irritation persists, consult a physician. |
| Ingestion | Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician. |

Material name: CF352A

| dispersed in air. Extinguishing media Suitable extinguishing media Unsuitable extinguishing In arc. C02, water, or dry chemical media Unsuitable extinguishing If fire occurs in the printer, treat as an electrical fire. equipment/instructions Specific methods None established. Hazardous combustion products Carbon monoxide and carbon dioxide. Products Considerations. Do not flush into surface water or sanitary sever system. See also section 13 D considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp doth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of i federal, state, and local regulations. 7. Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open fla Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Occupational exposure limits US. ACGIT htreshold Limit Values Components Ype Value Form Ttanium dioxide (CAS YPE Value Form Components Ype Value Form Compone | | | | |
|--|--|------------|--|--|
| dispersed in air. Extinguishing media Suitable extinguishing media Unsuitable extinguishing If a cocurs in the printer, treat as an electrical fire. If a cocurs in the printer, treat as an electrical fire. Fire fighting equipment/instructions Specific methods None established. Carbon monoxide and carbon dioxide. Products Carbon monoxide and carbon dioxide. Forducts Carbon monoxide and carbon dioxide. Carbon must be rated an explosion-prof. Fine powder can form explosive dust-air mixtures. Dispose of i federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Components Type Value Components Type Value Form Thanium dioxide (CAS TWA 10 mg/m3 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US OSHA table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Forther Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Resp | | | | |
| Suitable extinguishing media CO2, water, or dry chemical media Unsuitable extinguishing media None known. Fire fighting If fire occurs in the printer, treat as an electrical fire. equipment/instructions None established. Specific methods None established. Hazardous combustion products Carbon monoxide and carbon dioxide. Personal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated at explosion-prof. Fine powder can form explosive dust-air mixtures. Dispose of in federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Occupational exposure limits US. NIOSH Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Thanium dioxide (CAS PEL 15 mg/m3 13463-67-7) US. NIOSH Focket Guide to Chemical Hazards Components Type <td colspan="3">Like most organic material in powder form, toner can form explosive dust-air mixtures when finel dispersed in air.</td> | Like most organic material in powder form, toner can form explosive dust-air mixtures when finel dispersed in air. | | | |
| media Unsuitable extinguishing media None known. media If fire occurs in the printer, treat as an electrical fire. equipment/instructions None established. Hazardous combustion products Carbon monoxide and carbon dioxide. 6. Accidental Release Measures Descond minize dust generation and accumulation. Dersonal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of i federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep taiphty closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Decupational exposure limits US. ACGH Threshold Limit Values Components Type Components Type Thanium dioxide (CAS PEL 13 dis3-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Components Type Value Form (Trani | | | | |
| media If fire occurs in the printer, treat as an electrical fire. "ire fighting guipment/instructions None established. Specific methods None established. Garbon monoxide and carbon dioxide. Carbon monoxide and carbon dioxide. So Accidental Release Measures Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Dther information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated at explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of i federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open file Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Doccupational exposure limits US. ACGIH Threshold Limit Values Components Type Components Type Value Titanium dioxide (CAS TWA 10 mg/m3 13/463-67-7) US. NIGSH: Pocket Guide to Chemical Hazards Components Components Type Value Components Type | CO2, water, or dry chemical | | | |
| squipment/instructions None established. Specific methods None established. Azzardous combustion products Carbon monoxide and carbon dioxide. 6. Accidental Release Measures Minimize dust generation and accumulation. Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated an explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of i federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skin with adequate ventilation. Keep away from excessive heat, sparks, and open fla Storage 8. Exposure Controls / Personal Protection Decuptional exposure limits US. ACGIH Threshold Limit Values Components Type Thanium dioxide (CAS PEL 15 mg/m3 13463-67-7) US. NIOSH Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Components Type Value | | | | |
| Hazardous combustion products Carbon monoxide and carbon dioxide. 6. Accidental Release Measures Personal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated at explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of i federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open file Storage 8. Exposure Controls / Personal Protection Occupational exposure limits US. ACGIH Threshold Limit Values Components Type VIS. ACGIA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type VIS. NIOSH: Pocket Guide to Chemical Hazards Components Type VIS. Tonessee. OELs. Occupational Exposure Limits, Table Z1A Components Type VIS. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type VIS. Tennessee. OELs. Occupational Exposure Limits, Table Z1A | | | | |
| 6. Accidental Release Measures Personal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open file Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Do ong/mat Occupational exposure limits US. ACGIH Threshold Limit Values Components Type Value Titanium dioxide (CAS TWA 10 mg/m3 13463-67-7) US. NOSH: Pocket Guide to Chemical Hazards Components Components Type Value Components Type Value Components Type Value Components Type Value Components Type Valu | | | | |
| Personal precautions Minimize dust generation and accumulation. Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Solwly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of it federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open fla Resposure Controls / Personal Protection Storage Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from store at room temperature. 8. Exposure Controls / Personal Protection Components Occupational exposure limits US. ACGIH Threshold Limit Values Us. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Components Type Value Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components <t< td=""><td></td><td></td></t<> | | | | |
| Environmental precautions Do not flush into surface water or sanitary sewer system. See also section 13 D considerations. Other information Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated a explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open fla Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at noom temperature. 8. Exposure Controls / Personal Protection Occupational exposure limits US. ACGIH Threshold Limit Values Yalue Form Components Type Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total di 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Manophous silica (CAS TWA 6 mg/m3 7031-86-9) US. Seconder CAS Type Value Form US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Manophous silica (CAS TWA 6 mg/m3 7031-86 | | | | |
| Considerations. Slowly vacuum or sweep the material into a bag or other sealed container. Clea damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of i federal, state, and local regulations. 7. Handling and Storage Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open fla Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from store at room temperature. 3. Exposure Controls / Personal Protection Doccupational exposure limits US. ACGIH Threshold Limit Values Type Components Type VB. ACGIH Threshold Limit Values Components Components Type VIS. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Form Components Type VIS. NIOSH: Pocket Guide to Chemical Hazards Components Components Type VIS. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Gomponents USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Par | | | | |
| damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of it federal, state, and local regulations. 7. Handling and Storage Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open fla Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 3. Exposure Controls / Personal Protection Docupational exposure limits US. ACGIH Threshold Limit Values Type Components Type Components Type Value Form Titanium dioxide (CAS TWA 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value | 13 Disposal | | | |
| Handling Keep out of the reach of children. Avoid inhalation of dust and contact with skir with adequate ventilation. Keep away from excessive heat, sparks, and open flating store at room temperature. Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Value Occupational exposure limits Type Value Itanium dioxide (CAS TWA 10 mg/m3 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Value Form Components Type Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Yupe Value Amorphous silica (CAS TWA 6 mg/m3 7031-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) 13463-67-7) <td< td=""><td colspan="4">Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with</td></td<> | Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with | | | |
| with adequate ventilation. Keep away from excessive heat, sparks, and open fla Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Decupational exposure limits US. ACGIH Threshold Limit Values Value Components Type Value Titanium dioxide (CAS Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Form Titanium dioxide (CAS PEL 13463-67-7) 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Form Components Type Value Form Titanium dioxide (CAS PEL 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value Titanium dioxi | | | | |
| Storage Keep out of the reach of children. Keep tightly closed and dry. Store away from Store at room temperature. 8. Exposure Controls / Personal Protection Decupational exposure limits DS. ACGIH Threshold Limit Values Type Components Type Titanium dioxide (CAS TWA 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Form Titanium dioxide (CAS PEL 13463-67-7) 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Components Type Value Form Titanium dioxide (CAS PEL 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form Titanium dioxide (CAS TWA 0 mg/m3 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value Titanium dioxide (CAS TWA 10 mg/m3 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) | | es. Use | | |
| Occupational exposure limits US. ACGIH Threshold Limit Values Components Type Value Titanium dioxide (CAS TWA 10 mg/m3 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Form Components Type Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Morphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Form Components Type Value Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | oxidizers. | | |
| Occupational exposure limits US. ACGIH Threshold Limit Values Components Type Value Titanium dioxide (CAS TWA 10 mg/m3 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Form Components Type Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total detter 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Form Titanium dioxide (CAS TWA 10 mg/m3 Total detter 13463-67-7) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value Form Titanium dioxide (CAS TWA 10 mg/m3 Total det 13463-67-7) Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| US. ACGIH Threshold Limit Values Components Type Value Titanium dioxide (CAS TWA 10 mg/m3 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Form Components Type Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Value Morphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value Components Type Value Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 3463-67-7) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| ComponentsTypeValueTitanium dioxide (CAS 13463-67-7)TWA10 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) ComponentsComponentsTypeValueFormTitanium dioxide (CAS 13463-67-7)PEL15 mg/m3Total dUS. NIOSH: Pocket Guide to Chemical Hazards ComponentsTypeValueMamorphous silica (CAS 7631-86-9)TWA6 mg/m37631-86-9)US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A ComponentsTypeValueFormTitanium dioxide (CAS 13463-67-7)TWA10 mg/m3Total dJa463-67-7)USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| 13463-67-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Form Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Total d Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| ComponentsTypeValueFormTitanium dioxide (CAS 13463-67-7)PEL15 mg/m3Total dUS. NIOSH: Pocket Guide to Chemical Hazards ComponentsYalueTypeValueAmorphous silica (CAS 7631-86-9)TWA6 mg/m3FormUS. Tennessee. OELs. Occupational Exposure Limits, Table Z1A ComponentsYalueFormTitanium dioxide (CAS 13463-67-7)TWA10 mg/m3Total dTitanium dioxide (CAS 13463-67-7)TWA10 mg/m3Total dExposure guidelinesUSA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| Titanium dioxide (CAS PEL 15 mg/m3 Total d 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value Components Type Value Form Titanium dioxide (CAS TWA 10 mg/m3 Total d Total d 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) Total d | | | | |
| 13463-67-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 6 mg/m3 Components Type Value Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| ComponentsTypeValueAmorphous silica (CAS 7631-86-9)TWA6 mg/m3US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A ComponentsFormComponentsTypeValueFormTitanium dioxide (CAS 13463-67-7)TWA10 mg/m3Total dExposure guidelinesUSA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Par | tal dust. | | | |
| Amorphous silica (CAS TWA 6 mg/m3 7631-86-9) US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A Components Type Value Form Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| ComponentsTypeValueFormTitanium dioxide (CAS 13463-67-7)TWA10 mg/m3Total dExposure guidelinesUSA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | | |
| Titanium dioxide (CAS TWA 10 mg/m3 Total d 13463-67-7) USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate), 3 mg/m3 | rm | | | |
| Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction) ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | tal dust. | | | |
| | ion) | | | |
| Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACG) | ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate) | | | |
| mg/m3 | acgih (twa) | /TLV): 10 | | |
| Engineering controls Use in a well ventilated area. | | | | |
| Personal protective equipment General No personal respiratory protective equipment required under normal conditions | ions of use. | | | |

9. Physical & Chemical Properties

| 5. Thysical & chemical http | |
|------------------------------|---|
| Appearance | Fine powder |
| Physical state | Solid. |
| Form | solid |
| Color | Yellow |
| Odor | Slight plastic odor |
| рН | Not applicable |
| Vapor pressure | Not applicable |
| Boiling point | Not applicable |
| Melting point/Freezing point | Not available. |
| Solubility (water) | Negligible in water. Partially soluble in toluene and xylene. |
| Specific gravity | 1 - 1.2 |
| Flash point | Not applicable |
| Viscosity | Not applicable |
| Percent volatile | 0 % estimated |
| Softening point | 176 - 266 °F (80 - 130 °C) |
| VOC | Not available |
| Other information | No information available |
| Other data | |
| Decomposition temperature | > 392 °F (> 200 °C) |
| | alt de l'Esterne de la |

10. Chemical Stability & Reactivity Information

| Chemical stability | Stable under normal storage conditions. |
|---------------------------------------|---|
| Conditions to avoid | Imaging Drum: Exposure to light |
| Incompatible materials | Strong oxidizers |
| Hazardous decomposition products | Carbon monoxide and carbon dioxide. |
| Possibility of hazardous reactions | Will not occur. |

11. Toxicological Information

| Toxicological data | | | | |
|-------------------------------|---|--|--|--|
| Components | Species | Test Results | | |
| Amorphous silica (CAS 7631-86 | 5-9) | | | |
| Acute | | | | |
| Oral | | | | |
| LD50 | Mouse | > 15000 mg/kg | | |
| | Rat | > 22500 mg/kg | | |
| Sensitization | Not classified as a se HCS (US). | Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSHA HCS (US). | | |
| Chronic effects | No information availa | No information available. | | |
| Carcinogenicity | Titanium dioxide is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). The IARC classification was based on high concentrations of titanium dioxide particles in animal lungs. Under intended use of this toner product, exposure to titanium dioxide is much lower. | | | |
| | None of the other ingredients in this preparation are classified as carcinogens according EU, IARC, MAK, NTP or OSHA. | | | |
| ACGIH Carcinogens | | | | |
| TITANIUM DIOXIDE (| CAS 13463-67-7) | A4 Not classifiable as a human carcinogen. | | |

| IARC Monographs. Over | all Evaluation of Carcino | ogenicity | |
|---|---|--|--|
| Amorphous silica (CAS 7631-86-9) Titanium dioxide (CAS 13463-67-7) | | 3 Not classifiable as to carcinogenicity to humans. 2B Possibly carcinogenic to humans. | |
| Serious eye damage/eye irritation | Not classified as irritan Directive 67/548/EEC a | it, according to OSHA Hazard Communication Standard (HCS) and EU and as amended. | |
| Mutagenicity | Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium) | | |
| Reproductive effects | Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 65, and DFG (Germany). | | |
| Further information | Complete toxicity data are not available for this specific formulation Refer to Section 2 for potential health effects and Section 4 for first aid measures. | | |
| 12. Ecological Information | | | |

| Ecotoxicological data Product | | Species | Test Results | |
|--|---|--|--|--|
| CF352A | | | | |
| Fish | LC50 | Fish | > 100 mg/l, 96 Hours | |
| Components | | Species | Test Results | |
| Titanium dioxide (CAS 13463-67- | 7) | | | |
| Aquatic | | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | > 1000 mg/l, 48 hours | |
| Fish | LC50 | Mummichog (Fundulus heteroclitus) | > 1000 mg/l, 96 hours | |
| Ecotoxicity | LC50: > 100 | mg/l, Fish, 96.00 Hours | | |
| Persistence and degradability | Not available | | | |
| 13. Disposal Considerations | ; | | | |
| Disposal instructions | Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, sta and local regulations. | | | |
| | of HP origina | | ogram enables simple, convenient recycling information and to determine if this service o.com/recycle. | |
| 14. Transport Information | | | | |
| Further information | Not a danger | Not a dangerous good under DOT, IATA, ADR, IMDG, or RID. | | |
| 15. Regulatory Information | | | | |
| US federal regulations | US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA. | | | |
| Drug Enforcement Admin Chemical Code Number | istration (DEA |). List 2, Essential Chemicals (21 CFF | R 1310.02(b) and 1310.04(f)(2) and | |
| Not listed. Drug Enforcement Admin | istration (DEA |). List 1 & 2 Exempt Chemical Mixtur | res (21 CFR 1310.12(c)) | |
| Not regulated. DEA Exempt Chemical Mix | ctures Code N | umber | | |
| Not regulated. TSCA Section 12(b) Expor | t Notification | (40 CFR 707, Subpt. D) | | |
| Not regulated. | | | | |
| CERCLA (Superfund) reportat | le quantity | | | |
| Superfund Amendments and | Reauthorizatio | on Act of 1986 (SARA) | | |
| Hazard categories | Immediate H Delayed Haza Fire Hazard - Pressure Haz | azard - No ard - No No | | |

Reactivity Hazard - No

| SARA 302 Extremely hazardous substance | No | |
|---|--|--|
| SARA 311/312 Hazardous chemical | No | |
| Other regulations | under chemical substances no | HP product have been notified or are exempt from notification tification laws in the following countries: US (TSCA), EU , Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, |
| State regulations | | |
| US - California Propositio | n 65 - CRT: Listed date/Carci | nogenic substance |
| TITANIUM DIOXIDE (AI OF RESPIRABLE SIZE) ((| | Listed: September 2, 2011 Carcinogenic. |
| US - New Jersey RTK - Su | bstances: Listed substance | |
| Titanium dioxide (CAS 1. US. Massachusetts RTK - | | Listed. |
| Amorphous silica (CAS 7 Titanium dioxide (CAS 1 US. Pennsylvania RTK - H | 3463-67-7) | |
| Titanium dioxide (CAS 1. US. Rhode Island RTK | 3463-67-7) | Listed. |
| Titanium dioxide (CAS 1 | 3463-67-7) | |
| 16. Other Information | | - |
| HMIS® ratings | Health: 1 Flammability: 1 Physical hazard: 0 | |
| NFPA ratings | Health: 1 Flammability: 1 Instability: 0 | |
| Disclaimer | This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries. | |
| Other information | This MSDS was prepared in ac CFR 1910.1200). | cordance with USA OSHA Hazard Communications regulation (29 |
| Issue date | 08-Nov-2013 | |
| Manufacturer information | Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800 |)-457-4209 |

Explanation of abbreviations

| ACGIH | American Conference of Governmental Industrial Hygienists |
|--------|---|
| CAS | Chemical Abstracts Service |
| CERCLA | Comprehensive Environmental Response Compensation and Liability Act |
| | |
| CFR | Code of Federal Regulations |
| COC | Cleveland Open Cup |
| DOT | Department of Transportation |
| EPCRA | Emergency Planning and Community Right-to-Know Act (aka SARA) |
| IARC | International Agency for Research on Cancer |
| NIOSH | National Institute for Occupational Safety and Health |
| NTP | National Toxicology Program |
| OSHA | Occupational Safety and Health Administration |
| PEL | Permissible Exposure Limit |
| RCRA | Resource Conservation and Recovery Act |
| REC | Recommended |
| REL | Recommended Exposure Limit |
| SARA | Superfund Amendments and Reauthorization Act of 1986 |
| STEL | Short-Term Exposure Limit |
| TCLP | Toxicity Characteristics Leaching Procedure |
| TLV | Threshold Limit Value |
| TSCA | Toxic Substances Control Act |
| VOC | Volatile Organic Compounds |