

MATERIAL SAFETY DATA SHEET

1. Product and Company	Identification		
Material name	HP Color LaserJet CF359A Imaging Drum Cartridge		
Version #	01		
Issue date	08-Nov-2013		
Product use	This product is a cyan toner preparation that is used in HP Color LaserJet Enterprise flow MFF M880 series printers.		
Company identification	Hewlett-Packard Company 3000 Hanover Street Palo Alto, CA 94304-1185 United States Telephone 650-857-5020		
	Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209 (Direct) 1-760-710-0048 HP Customer Care Line (Toll-free within the US) 1-800-474-6836 (Direct) 1-208-323-2551 Email: hpcustomer.inquiries@hp.com		
2. Hazards Identification			
Potential health effects			
Eyes	May cause transient slight irritation		
Skin	Unlikely to cause skin irritation.		
Inhalation	Minimal respiratory tract irritation may occur with exposure to large amounts of toner dust. U this product as intended does not result in inhalation of excessive amounts of dust.		
Ingestion	Low acute toxicity. Ingestion is a minor route of entry for intended use of this product.		
Other hazards	This product is not classified as hazardous according to OSHA CFR 1910.1200 or EU Directive 1999/45/EC, as amended. None of the ingredients have been classified as carcinogens according to EU, IARC, MAK, NTP, OSHA or ACGIH.		

3. Composition / Information on Ingredients

Non-hazardous components	CAS #	Percent
Styrene acrylate copolymer	Trade Secret	<90
Pigment	Trade Secret	<10
Wax	Trade Secret	<10
Amorphous silica	7631-86-9	<3

4. First Aid Measures	
General advice	No information
First aid procedures	
Eye contact	Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for a least 15 minutes or until particles are removed. If irritation persists, consult a physician.
Skin contact	Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation develops or persists.
Inhalation	Move person to fresh air immediately. If irritation persists, consult a physician.
Ingestion	Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a physician.

5. Fire Fighting Measures			
Flammable properties	Like most organic material in powder form, toner can form explosive dust-air mixtures when finely dispersed in air.		
Extinguishing media Suitable extinguishing media	CO2, water, or dry chemical		
Unsuitable extinguishing media	None known.		
Fire fighting equipment/instructions	If fire occurs in the printer, treat as an electrical fire.		
Specific methods	None established.		
Hazardous combustion products	Carbon monoxide and carbon dioxide.		
6. Accidental Release Measu	ures		
Personal precautions	Minimize dust generation and accu	mulation.	
Environmental precautions	Do not flush into surface water or considerations.	sanitary sewer system. See also section 13 Disposal	
Other information	Slowly vacuum or sweep the material into a bag or other sealed container. Clean remainder with a damp cloth or vacuum cleaner. If a vacuum is used, the motor must be rated as dust explosion-proof. Fine powder can form explosive dust-air mixtures. Dispose of in compliance with federal, state, and local regulations.		
7. Handling and Storage			
Handling	Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames.		
Storage	Keep out of the reach of children. Keep tightly closed and dry. Store away from strong oxidizers. Store at room temperature.		
8. Exposure Controls / Pers	onal Protection		
Occupational exposure limits			
US. NIOSH: Pocket Guide Components	to Chemical Hazards Type	Value	
Amorphous silica (CAS 7631-86-9)	TWA	6 mg/m3	
Exposure guidelines	USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)		
	ACGIH (TWA/TLV): 10 mg/m3 (Inl	nalable Particulate), 3 mg/m3 (Respirable Particulate)	
	Amorphous silica: USA OSHA (TW mg/m3	A/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10	
Engineering controls	Use in a well ventilated area.		
Personal protective equipmen General		equipment required under normal conditions of use.	
9. Physical & Chemical Prop	perties		
Appearance	Fine powder		
Physical state	Solid.		
Form	solid		
Color	Cyan		
Odor	Slight plastic odor		
рН	Not applicable		
Vapor pressure	Not applicable		
	Not applicable		
Boiling point	Not applicable Not available.		

Material name: CF359A

Ecotoxicological data	Species		
Further information 12. Ecological Information	Complete toxicity data are not available for this specific formulation Refer to Section 2 for potential health effects and Section 4 for first aid measures.		
Reproductive effects	Not classified as toxic according to EU Directive 67/548/EEC and as amended, California Prop. 6 and DFG (Germany).		
Mutagenicity	Negative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)		
Serious eye damage/eye irritation	Not classified as irritant, according to OSHA Hazard Communication Standard (HCS) and EU Directive 67/548/EEC and as amended.		
Amorphous silica (CAS	7631-86-9)	3 Not classifiable as to carcinogenicity to humans.	
	all Evaluation of Carcinogenic	ity	
Carcinogenicity	Not a known or suspected carcinogen according to any IARC Monograph, NTP, OSHA Regulation (USA), EU Directive, or Proposition 65 (California).		
Chronic effects	No information available.		
Sensitization	Not classified as a sensitizer according to EU Directive 67/548/EEC and as amended, and OSH/ HCS (US).		
	Rat	> 22500 mg/kg	
LD50	Mouse	> 15000 mg/kg	
Oral			
Acute			
Amorphous silica (CAS 7631-86-	•		
Toxicological data Components	Species	Test Results	
11. Toxicological Informat	tion		
Possibility of hazardous reactions	Will not occur.		
products			
Incompatible materials Hazardous decomposition	Strong oxidizers Carbon monoxide and carbon	diovide	
	Imaging Drum: Exposure to li	gnt	
Chemical stability Conditions to avoid	Stable under normal storage		
10. Chemical Stability & R	•	100	
temperature	as ativity Information		
Decomposition	> 392 °F (> 200 °C)		
Other data			
Other information	No information available		
voc	Not available		
Softening point	176 - 266 °F (80 - 130 °C)		
Percent volatile	0 % estimated		
Viscosity	Not applicable		
Flash point	Not available. Not applicable		
Specific gravity			

Ecotoxicological aata			
Product		Species	Test Results
CF359A			
Fish	LC50	Fish	> 100 mg/l, 96 Hours
Ecotoxicity	LC50: > 100 n	ng/l, Fish, 96.00 Hours	
Persistence and degradability	Not available.		

13. Disposal Considerations			
Disposal instructions	Do not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state, and local regulations.		
	HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.		
14. Transport Information			
Further information	Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.		
15. Regulatory Information			
US federal regulations	US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA.		
Chemical Code Number	tration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and		
-	tration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))		
Not regulated. DEA Exempt Chemical Mixt	tures Code Number		
Not regulated.	Notification (40 CFR 707, Subpt. D)		
Not regulated.			
CERCLA (Superfund) reportable	e quantity		
None			
	eauthorization Act of 1986 (SARA)		
Hazard categories	Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazardous substance	Νο		
SARA 311/312 Hazardous chemical	No		
Other regulations	All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China.		
State regulations			
US. Massachusetts RTK - S			
Amorphous silica (CAS 76. US. Pennsylvania RTK - Ha	•		
Not regulated. US. Rhode Island RTK Not regulated.			
16. Other Information			
HMIS® ratings	Healthy 1		
Traings	Health: 1 Flammability: 1 Physical hazard: 0		
NFPA ratings	Health: 1 Flammability: 1 Instability: 0		

Disclaimer	This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
Other information	This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29 CFR 1910.1200).
Issue date	08-Nov-2013
Manufacturer information	Hewlett-Packard Company 11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199 (Toll-free within the US) 1-800-457-4209

Explanation of abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds