

1. Chemical Product and Company Identification

Matarial name			
Material name	Q7457A		
Use of the preparation	Inkjet printing		
Version #	05		
Revision date	26-Mar-2008		
CAS #	Mixture		
Product use	Inkjet printing		
Manufacturer information	Hewlett-Packard Company 1000 NE Circle Boulevard Corvallis, OR 97330-4239 US		
Hewlett-Packard health effec	ts line		
(Toll-free within the US) (Direct)	1-800-457-4209 1-503-494-7199		
General information telephon	ne number		
HP Customer Care Line (Toll-free) (Direct)	1-800-474-6836 1-800-474-6836 1-208-323-2551		
Date prepared	Mar 26, 2008		
MSDS number	255422		
lazards Identification			
Emergency overview	Contact with skin and eyes may result in irritation.		
	<i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness.		
Acute health effects	<i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or		
	<i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness.		
Acute health effects	<i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness.		
Acute health effects	<i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness. Any potential hazards are presumed to be due to exposure to the components. <i>2-pyrrolidone</i>		
Acute health effects Skin contact	<i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness. Any potential hazards are presumed to be due to exposure to the components. <i>2-pyrrolidone</i>		
Acute health effects Skin contact	 <i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness. Any potential hazards are presumed to be due to exposure to the components. <i>2-pyrrolidone</i> Contact with skin may result in irritation. <i>2-pyrrolidone</i> 		
Acute health effects Skin contact	 <i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness. Any potential hazards are presumed to be due to exposure to the components. <i>2-pyrrolidone</i> Contact with skin may result in irritation. <i>2-pyrrolidone</i> Contact with eyes may result in irritation. <i>Isopropyl Alcohol</i> 		
Acute health effects Skin contact Eye contact	 <i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness. Any potential hazards are presumed to be due to exposure to the components. <i>2-pyrrolidone</i> Contact with skin may result in irritation. <i>2-pyrrolidone</i> Contact with eyes may result in irritation. <i>Isopropyl Alcohol</i> 		
Acute health effects Skin contact Eye contact	 <i>Isopropyl Alcohol</i> Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness. Any potential hazards are presumed to be due to exposure to the components. <i>2-pyrrolidone</i> Contact with skin may result in irritation. <i>2-pyrrolidone</i> Contact with eyes may result in irritation. <i>Isopropyl Alcohol</i> Contact with eyes may result in severe irritation. <i>2-pyrrolidone</i> 		
Acute health effects Skin contact Eye contact	Isopropyl Alcohol Contact with skin and eyes may result in irritation. Inhalation may cause drowsiness or dizziness. Any potential hazards are presumed to be due to exposure to the components. 2-pyrrolidone Contact with skin may result in irritation. 2-pyrrolidone Contact with eyes may result in irritation. Isopropyl Alcohol Contact with eyes may result in severe irritation. Isopropyl Alcohol Contact with eyes may result in respiratory irritation. Isopropyl Alcohol Inhalation may result in respiratory irritation.		



Potential health effects Routes of exposure	Potential routes of overexposure to this product are skin and eye contact
	Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this product under normal use conditions.
	Complete toxicity data are not available for this specific formulation
	<i>Isopropyl Alcohol</i> Potential routes of exposure under normal use conditions are skin, eye contact and inhalation.
Chronic health effects	Carbon Black: Chronic inhalation studies performed with fine dust particles resulted in lung tumors in animals. The IARC classification was based upon these results. IARC also concluded "there is inadequate evidence in humans for the carcinogenicity of carbon black." Inhalation of fine dust particles is not expected to occur during normal conditions of use of this ink.
Carcinogenicity	Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.
Other information	
	<i>Isopropyl Alcohol</i> This product is classified for health and physicochemical effects according to EU Directive 1999/45/EC with R11, R36 and R67.

3. Composition / Information on Ingredients

Component/substance	C	AS number	% by weight
Water	77	732-18-5	> 70
2-pyrrolidone	61	16-45-5	< 15
Carbon black	13	333-86-4	< 5
Isopropyl Alcohol	67	7-63-0	< 5
Composition comments	This ink supply contains an aqueous ink formulation. This product has been evaluated using criteria specified in 29 CFR 1910.1200 (Hazard Communication Standard).		
I. First Aid Measures			
First aid procedures			
Eye contact	for at least 15 minutes of Do not rub eyes, Immed	or until particles are rer liately flush with large	amounts of clean, warm water (low pressure) moved. If irritation persists get medical attentio amounts of clean, warm water (low pressure) moved, If irritation persists get medical attentio
Skin contact	Wash affected areas thoroughly with mild soap and water. If irritation persists get medical attention. Wash affected areas thoroughly with mild soap and water and Get medical attentior if irritation develops or persists.		
Inhalation	Move to fresh air. If symptoms persist, get medical attention. Move to fresh air, If symptoms persist, get medical attention.		
Ingestion	If ingestion of a large amount does occur, seek medical attention. If ingestion of a large amount does occur, seek medical attention.		
5. Fire Fighting Measures			
Flash point and method			Closed Cup; No ignition, sustained combustion tibility Test (method in US 49CFR173, Appendi



Hazardous combustion products	Refer to section 10. Carbon monoxide and carbon dioxide.		
Flammable properties	None known. Flammable Liquid and Will burn if involved in a fire and Vaporizes easily at normal temperatures and Vapors may travel to a source of ignition and flash back.		
Extinguishing media			
Suitable extinguishing media	CO2, water, dry chemical, or foam Dry chemical, CO2, water spray or regular foam.		
Unsuitable extinguishing media	None known. None known.		
Unusual fire and explosion hazard	None known. Flammable Liquid and Will burn if involved in a fire and Vaporizes easily at normal temperatures and Vapors may travel to a source of ignition and flash back.		
Protection of firefighters			
Specific hazards arising from the chemical	None known		
Special firefighting procedures	None established.		
6. Accidental Release Measure	S		
Personal precautions	Wear appropriate personal protective equipment. Wear appropriate personal protective equipment and Ensure adequate ventilation and Remove all sources of ignition.		
Environmental precautions	Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Do not let product enter drains and Do not flush into surface water or sanitary sewer system.		
Other information	Soak up with inert absorbent material. Slowly vacuum or sweep the material into a bag or other sealed container. Dispose of in compliance with federal, state, and local regulations. See also section 13 Disposal considerations. Soak up with inert absorbent material, Clean remainder with a damp cloth or vacuum cleaner, Dispose of in compliance with federal, state, and local regulations, See also section 13 Disposal considerations.		
7. Handling and Storage			
Handling	Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition and Avoid contact with skin and eyes Use this product with adequate ventilation.		
Storage	Keep out of the reach of children. Keep away from excessive heat or cold. Keep away from		

8. Exposure Controls/Personal Protection

osure limits				
ACGIH				
Components	CAS #	TWA	STEL	Ceiling
Carbon black	1333-86-4	3.5 mg/m3	Not established	Not established
Isopropyl Alcohol	67-63-0	200 ppm	400 ppm	Not established
OSHA				
Components	CAS #	TWA	STEL	Ceiling
Carbon black	1333-86-4	3.5 mg/m3	Not established	Not established
Isopropyl Alcohol	67-63-0	400 ppm	Not established	Not established

excessive heat, sparks, and open flames.

MATERIAL SAFETY DATA SHEET

Exposure guidelines	Exposure limits have not been established for this product.			
ACGIH - Threshold Limits Values - Isopropyl Alcohol	Time Weighted Averag 67-63-0	es (TLV-TWA) 200 ppm TWA		
ACGIH - Threshold Limits Values - Carbon black	its Values - Time Weighted Averages (TLV-TWA) 1333-86-4 3.5 mg/m3 TWA			
U.S OSHA - Final PELs - Time We	eighted Averages (TWA	us)		
Carbon black	1333-86-4	3.5 mg/m3 TWA		
U.S OSHA - Final PELs - Time We	eighted Averages (TWA	vs)		
Isopropyl Alcohol	67-63-0	400 ppm TWA; 980 mg/m3 TWA		
Personal protective equipment				
General	Use personal protective equipment to minimize exposure to skin and eye. Use personal protective equipment to minimize exposure to skin and eye.			
Eye / face protection	Not required under intended use.			
Skin protection	Protected gloves not required under intended use.			
Respiratory protection	For use other than intended use (such as in the event of a large spill), goggles and respirators may be required.			
General hygeine considerations		e with good industrial hygiene and safety practice. Handle in accordance hygiene and safety practice.		

9. Physical & Chemical Properties

Color	Black
Odor threshold	no appreciable odor
Physical state	Liquid.
рН	7.8 - 8.4
Melting point	Not available
Freezing point	Not available
Boiling point	> 200 °F (> 93.3 °C)
Flash point	131 - 136 °F (55 - 57.8 °C); Pensky-Martens Closed Cup; No ignition, sustained combustion or flashing detected using the Sustained Combustibility Test (method in US 49CFR173, Appendix H).
Evaporation rate	Not determined
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available
Flammability limits in air, lower, % by volume	Not available
Vapor pressure	Not determined
Vapor density	> 1 (air = 1.0)
Specific gravity	1 - 1.2 g/mL
Relative density	Not available
Solubility in water	Soluble in water
Partition coefficient (n-octanol/water)	Not determined
Auto-ignition temperature	Not available



Decomp	osition temperature	Not available			
VOC		< 3 %			
Viscosit	у	> 2 cp			
Bulk de	nsity	1 - 1.2 gm/ml			
10. Chemic	al Stability & Reactiv	ity Information			
Chemica	al stability	Stable under recommended storage conditions. Stable under recommended storage conditions			
Incomp	atible materials	Incompatible with strong bases and oxidizing agents. Incompatible with strong acids and bases.			
Hazardo product	ous decomposition s	Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Carbon monoxide and carbon dioxide.			
Possibil reactior	ity of hazardous Is	Will not occur. Will not occur.			
11. Toxico	ogical Information				
Carcino	genicity				
	6HA - Hazard Communicati Ion black	on Carcinogens 1333-86-4	Present		
Sympto	ms and target organs				
	Pocket Guide - Target Org ropyl Alcohol	ans 67-63-0	eyes, skin, respiratory system		
	Pocket Guide - Target Org on black	ans 1333-86-4	respiratory system, eyes (lymphatic cancer in presence of PAHs)		
12. Ecologi	ical Information				
Aquatic	toxicity	LC50/96h/Fathead minnows =>750 mg/L LC50/96h/Fathead minnows =9460 mg/L. EC50/48h/daphnia =13299 mg/L. EC50/72h/algae =/> 1000 mg/L.			
Persiste	ence and degradability	Not available			
Partitio	n coefficient	Not determined			
13. Dispos	al Considerations				
Disposa	l instructions	Dispose of in compliance with federal, state, and local regulations. HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle. Dispose of in compliance with federal, state, and local regulations.			

14. Transportation Information

Department of Transportation (DOT) Requirements

Not regulated as hazardous goods.



IATA

Proper shipping name	Not applicable		
Hazard class	Not applicable		
UN number	None		
Packing group	N/A		
Packaging exceptions	None		
6. Regulatory Information			
US federal regulations	US TSCA 12(b): Cont requirements.	ains tetrahydrofuran (CASRN 109-99-9), subject to export notification	
U.S CERCLA/SARA - Section 313 Isopropyl Alcohol	- Emission Reporting 67-63-0	1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)	
CERCLA (Superfund) reportabl	e quantity		
None			
Superfund Amendments and R	eauthorization Act o	of 1986 (SARA)	
Hazard categories	Immediate Hazard - I Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - N	No	
Section 302 extremely hazardous substance	No		
Section 311 hazardous chemical	No		
International regulations	under chemical subst (EINECS/ELINCS), Sv New Zealand, and Ch exempt from notificat countries: US (TSCA	tes in this HP product have been notified or are exempt from notification tances notification laws in the following countries: US (TSCA), EU witzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Kor nina. All chemical substances in this HP product have been notified or ar tion under chemical substances notification laws in the following .), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, buth Korea, New Zealand, and China.	
State regulations			
U.S California - Proposition 65 - 0	Carcinogens List		
Carbon black	1333-86-4	carcinogen, initial date 2/21/03 (airborne, unbound particles of respirable size)	
U.S Pennsylvania - RTK (Right to Isopropyl Alcohol	Know) List 67-63-0	Environmental hazard	
U.S Pennsylvania - RTK (Right to Carbon black	Know) List 1333-86-4	Present	
U.S New Jersey - Right to Know Carbon black	Hazardous Substance l 1333-86-4	List sn 0342	
U.S New Jersey - Right to Know Isopropyl Alcohol	Hazardous Substance l 67-63-0	List sn 1076; sn 2381 (strong-acid process manufacture)	

16. Other Information

HMIS® ratings

Health: 1 Flammability: 2 Physical hazard: 0



NFPA ratings	Health: 1 Flammability: 2 Instability: 0
Issue date	Mar 26 2008 1:02PM
Revision	5
Replaces sheet dated	Dec 15 2007 4:19PM
Disclaimer	This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.
MSDS sections updated	 Hazards Identification: Chronic health effects Hazards Identification: Carcinogenicity Exposure Controls/Personal Protection: Respiratory Regulatory Information: Canadian regulations
Explanation of abbreviations	
ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
COC	Cleveland Open Cup
DOT	Department of Transportation
EPCRA	Emergency Planning and Community Right-to-Know Act (aka SARA)
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation and Recovery Act
REC	Recommended
REL	Recommended Exposure Limit
SARA	Superfund Amendments and Reauthorization Act of 1986
STEL	Short-Term Exposure Limit
TCLP	Toxicity Characteristics Leaching Procedure
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
VOC	Volatile Organic Compounds